Aberystwyth University

Impact of anionic and cationic surfactants interfacial tension on the oil recovery enhancement

Pan, Fei; Zhang, Zaixu; Zhang, Xiaoxuan; Davarpanah, Afshin

Published in:
Powder Technology

DOI:
[10.1016/j.powtec.2020.06.033](https://doi.org/10.1016/j.powtec.2020.06.033)

Publication date:
2020

Citation for published version (APA):

Pan, F., Zhang, Z., Zhang, X., & Davarpanah, A. (2020). Impact of anionic and cationic surfactants interfacial tension on the oil recovery enhancement. *Powder Technology*, 373, 93-98.
<https://doi.org/10.1016/j.powtec.2020.06.033>

Document License CC BY-NC-ND

General rights

Copyright and moral rights for the publications made accessible in the Aberystwyth Research Portal (the Institutional Repository) are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the Aberystwyth Research Portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the Aberystwyth Research Portal

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

tel: +44 1970 62 2400
email: is@aber.ac.uk

Impact of Anionic and Cationic Surfactants Interfacial Tension on the Oil Recovery Enhancement

Fei Pan ^{1,2*}, Zaixu Zhang ¹, Xiaoxuan Zhang³, Afshin Davarpanah^{4*}

¹*School of Economics and Management, China University of Petroleum (East China), Qingdao City, Shandong Province, 266580, China*

²*Enterprise Management Department, Sinopec Shengli Oil field Company, Dongying City, Shandong Province, 257000, China*

³*Equipment Management Department, Sinopec Shengli Oil field Company, Dongying City, Shandong Province, 257000, China*

⁴*Department of Mathematics, Aberystwyth University, Aberystwyth, SY23 3FL, UK*
Correspondence to AD (afd6@aber.ac.uk) and FP (pandegre@163.com)

Abstract

In this paper, a cationic surfactant of Cetyl trimethyl ammonium bromide and an anionic surfactant of linear alkylbenzene sulfonic acid were used to consider their effect on the interfacial tension and oil recovery factor. According to the results of this study, the anionic surfactant of linear alkylbenzene sulfonic acid has the highest recovery factor of 70%, and cationic surfactant of Cetyl trimethyl ammonium bromide has the second-highest oil recovery factor of about 55%. Therefore, the addition of surfactants due to its beneficial impact on the interface adsorption between oil and water would be an essential point on the oil recovery enhancement. Moreover, the critical micelle concentration value is about 300 ppm and 250 ppm for anionic and cationic surfactants respectively where the two crosslines meet each other and anionic has the highest interfacial tension rather than cationic which has caused to have more oil recovery factor.

Keywords: Interfacial Tension, Critical Micelle Concentration, Surfactant Flooding, Oil Recovery Factor, Capillary Number, Wettability Alteration

1. Introduction

Due to the vitally essential needs of several industries to crude oil for their industrial purposes, petroleum industries have always try to find efficient techniques to enhance oil production rate(Lake et al., 2014; Masnadi et al., 2018; Alipour et al., 2017; Davarpanah et al., 2018). As conventional methods have been weakened bypassing the production time, it is of importance to invent and try novel methods to produce more oil volumes in a cost-efficient way(Patel et al., 2019; Chanioti and Tzia, 2019; Al-Nakhli et al., 2016; Davarpanah et al., 2019). Mobility ratio and capillary number are substantial parameters that considerably influence the enhanced oil recovery processes. Mobility ration reduction and increase of capillary number have caused the lower interfacial tension which considered as one of the crucial parameters on the oil recovery enhancement(Nwidee et al., 2016; Druetta and Picchioni, 2019; Sivasankar and Kumar, 2018; Davarpanah and Mirshekari, 2019c). Chemical flooding, the mixture of technologies as they are more compatible with the reservoir characteristics or regarding their efficiency on special occasions after the secondary recovery methods(Bai et al., 2017; Sun et al., 2018; Guo et al., 2017; Davarpanah, 2018).

Surfactant flooding is considered as one of the efficient chemical enhanced oil recovery techniques in recent decades as it has the potential ability to alter the wettability and reduce the interfacial tension of water-oil. Another reason of using surfactant in oil recovery techniques is related to the low-cost and non-hazardous for the environment(Wang et al., 2017; Lu and Pope, 2017; Alzahid et al., 2019; Davarpanah and Mirshekari, 2019b). In general, surfactants are divided into four main categories of cationic, anionic, amphoteric, and nonionic due to their water dissociation. Regarding the environmental issues and economic aspects of natural surfactants rather than synthetic surfactants, it has widely reported in the literature(Nouqabi et al., 2017; Szaniawska et al., 2017; Rieger, 2017; Davarpanah and Mirshekari, 2019a).

USBM and Amott techniques have been used for several years to measure the wettability alteration in carbonate rocks as they are concentrated on the wettability state alteration. Therefore, wettability alteration is one of the substantial and unique for each reservoir (Okasha et al., 2007). Seethepalli et al. (2004) proposed an investigation on the anionic surfactants on the wettability alteration of carbonate rocks. They conducted some experiments on the interfacial tension, phase behaviour, wettability alteration, and adsorption for anionic surfactants. Therefore, anionic surfactants can change the wettability state of calcite surfaces from oil-wet to water-wet. Its performance was better than cationic surfactants (Seethepalli et al., 2004). According to the experimental evaluation of Jackson and Vinogradov (2012) on the profound impact of wettability alteration in carbonate reservoirs, they used potential streaming measurements to predict the core samples wettability, and it could change the wetting states (oil-wet, water-wet) and surface charges. They concluded that regarding the excess charge that is transported by the brine flow, the significant contrast was investigated between non-aged and aged samples (Jackson and Vinogradov, 2012). Smart water injection in order to enhance oil recovery regarding the ionic composition and desired salinity ranges for different salts is of importance. Alghamdi et al. (2019) investigated the synergistic effects of several brines to predict the wettability alteration state in carbonate reservoirs. They concluded that Na_2SO_4 is strongly recommended for wettability alteration on carbonate reservoirs (Alghamdi et al., 2019). Mahani et al. (2017) done some experimental investigation on the effect of temperature on the wettability alteration in carbonate reservoirs. They investigated dolomite and limestone core samples in different salinities and reservoir estimation temperature. They showed that dolomite has better wettability improvement rather than limestones in high temperature, which is corresponded to their rock type and mineralogy (Mahani et al., 2017).

Kamal et al. (2015) investigated the considerable influence of carboxy betaine surfactant, which is based on the propoxylated anionic and amphoteric surfactant on the increase of the capillary number and interfacial tension decrease. They concluded that anionic surfactant had provided lower interfacial tension rather than amphoteric surfactant. Moreover, they showed that anionic surfactants have higher thermal stability in long term processes (Kamal et al., 2015). Ahmadi et al. (2015) experimentally investigated a new natural surfactant that is extracted from roots of *Glycyrrhiza Glabra* on the oil recovery enhancement as it is low-cost and environmentally-friendly. They concluded that higher concentration of this natural surfactant had caused to more oil recovery factor rather than brine injection (Ahmadi et al., 2015).

We aimed to investigate the considerable influence of a cationic surfactant of Cetyl trimethyl ammonium bromide and an anionic surfactant of linear alkylbenzene sulfonic acid on the interfacial tension and oil recovery factor. Therefore, the addition of surfactants due to its beneficial impact on the interface adsorption between oil and water would be an important point on the oil recovery enhancement as it can increase the oil recovery factor.

2. Materials and Methods

2.1. Materials

In this paper, crude oil was selected from one of the Iranians oilfields in the south-west of Iran. Properties of crude oil that are used in this experiment is statistically depicted in Table 1. To be more reliable, the formation of brine components are the same as reservoir condition with the following composition and salinity as it is statistically explained in Table 2.

Chemicals Formula; in this experiment, a cationic surfactant of Cetyl trimethyl ammonium bromide (henceforth; CTAB) and an anionic surfactant of linear alkylbenzene sulfonic acid (henceforth; LABSA) were used. Cetyltrimethylammonium bromide $[(C_{16}H_{33})N(CH_3)_3Br]$ is a

quaternary ammonium surfactant of the antiseptic cetrimide. Linear alkylbenzene sulfonic acid $[\text{CH}_3(\text{CH}_2)_{11}\text{C}_6\text{H}_4\text{SO}_3\text{H}]$ is one of the approximately low costs with the greatest synthetic volume of surfactant with the high performance that is dried as the stable powder. Both of the utilized surfactants are compatible with the environment due to their straight chains.

2.2. Core flooding apparatus

The components of coreflood apparatus contained core holder which is supplied with the various fluids by displacement pumps that are located in horizontal section, and the core plug is placed through the core holder to allow the fluids at the input or output at determined pressure and temperature, foam generator, and fluid accumulators. The operational temperature, which is used in this experiment is 42 °C to be more adapted with the reservoir circumstances. The schematic of the core flooding setup is shown in Figure 1.

The core flooding procedure is described in more detail in Table 4.

3. Results and Discussion

3.1. Contact angle

Hydrostatic forces, electrostatic forces, and rock morphology are considered as influential parameters in the prediction of wettability changes phenomenon. Therefore, surfactants can change the wettability to water-wet or immediate wet, which helps to mobilize the entrapped oil in the porous media (Standnes and Austad, 2000). To measure contact angle, drop shape analyzer was used by cutting the core samples into small pieces of 3.8 cm in diameter and thickness of 0.2 cm. This operation was done by trimming machine and then to have relatively flat surfaces it was polished by end face grinder. Finally, the contact angle was measured and recorded. To measure

the effect of surfactants, the small pieces were put into crude oil for 14 days, as it needed to be completely oil-wet. It is schematically depicted in Figure 2.

To consider the effect of each surfactant concentration on the contact angle, different concentrations of Cetyl trimethyl ammonium bromide (CTAB) and linear alkylbenzene sulfonic acid (LABSA) were investigated. It is plotted in Figure 3.

As can be seen in Figure 3, the contact angle has been decreased by the increase of surfactant concentration. When there is no surfactant addition, the contact angle is measured approximately 140 °. In the first steps of surfactant addition, the contact angle decrease is prolonged; however, linear alkylbenzene sulfonic acid more intangible to change the wettability rather than the Cetyl trimethyl ammonium bromide.

3.2. Interfacial Tension Measurement

The interfacial tension between water and oil phase would play a substantial role in oil recovery enhancement due to the capillary number increase. Addition of surfactants has caused a dramatic decrease in the interfacial of water-oil. Thereby, the capillary number has increased and has caused to enhance oil mobilization in the porous media. Pendant drop method was used to measure the interfacial tension between the oil and aqueous phase, and the experimental tests were done in the temperature of 25°C. Impact of two surfactants on the interfacial tension had been investigated on different concentration. As it is evident in Figure 4, for two surfactants, due to the increase of surfactant concentration, there was a dramatic decrease on the interfacial tension of water-oil as it is expected that surface-active monomers were adsorbed and it had cause to more oil mobilization in the porous media. In higher surfactant concentrations, interfacial tension value has reached its minimum value. At this point, there were no significant changes in the interfacial tension which is known as critical micelle concentration (henceforth; CMC) which was illustrated by previous

researchers(Shen et al., 2017; Karimi et al., 2012; Hezave et al., 2013). To measure the critical micelle concentration for two surfactants, conductivity method was used. In this experiment, the CMC value is about 300 ppm and 250 ppm for LABSA and CTAB, respectively, where the two crosslines meet each other.

3.3. Oil Recovery

Surfactants regarding their ability to alter the wettability have played a substantial role in the oil mobilization. Figure 5 indicated the oil recovery factor for three different scenarios of water flooding, water-LASBA, and water-CTAB flooding. In the first period of pore volume injection (up to 0.5 pore volume), there is not any significant difference between the three scenarios as the surfactant concentration is not high enough. Since then, it had increased for surfactant scenarios, and water flooding had witnessed a stable pattern after one pore volume injection as the porous media is water-wet, and it had occupied high permeable pores. LASBA has the highest recovery factor of 70%, and CTAB has the second-highest oil recovery factor of about 55%. Therefore, the addition of surfactants due to its beneficial impact on the interface adsorption between oil and water would be an essential point on the oil recovery enhancement as it can increase the oil recovery factor.

4. Conclusions

Surfactants regarding their ability to alter the wettability have played a substantial role in the oil mobilization. The main conclusions of this study are as follows;

- The CMC value is about 300 ppm and 250 ppm for LABSA and CTAB, respectively, where the two crosslines meet each other.
- LASBA has the highest interfacial tension rather than CTAB, which has caused to have more oil recovery factor.

- LASBA has the highest recovery factor of 70%, and CTAB has the second-highest oil recovery factor of about 55%. Therefore, the addition of surfactants due to its beneficial impact on the interface adsorption between oil and water would be an essential point on the oil recovery enhancement as it can increase the oil recovery factor.
- Linear alkyl benzene sulfonic acid (LABSA) more intangible to change the wettability rather than the Cetyl trimethyl ammonium bromide (CTAB).

Conflict of Interest Statement

Funding: There is no financial support to do this experiment.

Conflict of Interest: The authors declare that they have no conflict of interest.

References

- Ahmadi MA, Galedarzadeh M and Shadizadeh SR. (2015) Wettability Alteration in Carbonate Rocks by Implementing New Derived Natural Surfactant: Enhanced Oil Recovery Applications. *Transport in porous media* 106: 645-667.
- Al-Nakhli AR, Sukkar LA, Arukhe J, et al. (2016) In-situ steam generation a new technology application for heavy oil production. *SPE Heavy Oil Conference and Exhibition*. Society of Petroleum Engineers.
- Alghamdi AO, Abu-Al-Saud MO, Al-Otaibi MB, et al. (2019) Electro-kinetic induced wettability alteration in carbonates: Tailored water chemistry and alkali effects. *Colloids and Surfaces A: Physicochemical and Engineering Aspects* 583: 123887.
- Alipour M, Hafezi R, Amer M, et al. (2017) A new hybrid fuzzy cognitive map-based scenario planning approach for Iran's oil production pathways in the post-sanction period. *Energy* 135: 851-864.
- Alzahid YA, Mostaghimi P, Walsh SD, et al. (2019) Flow regimes during surfactant flooding: The influence of phase behaviour. *Fuel* 236: 851-860.
- Bai M, Zhang Z, Cui X, et al. (2017) Studies of injection parameters for chemical flooding in carbonate reservoirs. *Renewable and Sustainable Energy Reviews* 75: 1464-1471.
- Chanioti S and Tzia C. (2019) Evaluation of ultrasound assisted and conventional methods for production of olive pomace oil enriched in sterols and squalene. *LWT* 99: 209-216.
- Davarpanah A. (2018) A feasible visual investigation for associative foam > polymer injectivity performances in the oil recovery enhancement. *European Polymer Journal* 105: 405-411.
- Davarpanah A and Mirshekari B. (2019a) Experimental Investigation and Mathematical Modeling of Gas Diffusivity by Carbon Dioxide and Methane Kinetic Adsorption. *Industrial & Engineering Chemistry Research* 58: 12392-12400.

- Davarpanah A and Mirshekari B. (2019b) Numerical simulation and laboratory evaluation of alkali–surfactant–polymer and foam flooding. *International Journal of Environmental Science and Technology*.
- Davarpanah A and Mirshekari B. (2019c) Sensitivity analysis of reservoir and rock properties during low salinity water injection. *Energy Reports* 5: 1001-1009.
- Davarpanah A, Mirshekari B, Jafari Behbahani T, et al. (2018) Integrated production logging tools approach for convenient experimental individual layer permeability measurements in a multi-layered fractured reservoir. *Journal of Petroleum Exploration and Production Technology* 8: 743-751.
- Davarpanah A, Shirmohammadi R, Mirshekari B, et al. (2019) Analysis of hydraulic fracturing techniques: hybrid fuzzy approaches. *Arabian Journal of Geosciences* 12: 402.
- Druetta P and Picchioni F. (2019) Influence of the polymer degradation on enhanced oil recovery processes. *Applied Mathematical Modelling* 69: 142-163.
- Guo H, Dou M, Hanqing W, et al. (2017) Proper use of capillary number in chemical flooding. *Journal of Chemistry* 2017.
- Hezave AZ, Dorostkar S, Ayatollahi S, et al. (2013) Investigating the effect of ionic liquid (1-dodecyl-3-methylimidazolium chloride ([C12mim][Cl])) on the water/oil interfacial tension as a novel surfactant. *Colloids and Surfaces A: Physicochemical and Engineering Aspects* 421: 63-71.
- Jackson MD and Vinogradov J. (2012) Impact of wettability on laboratory measurements of streaming potential in carbonates. *Colloids and Surfaces A: Physicochemical and Engineering Aspects* 393: 86-95.
- Kamal MS, Sultan AS and Hussein IA. (2015) Screening of amphoteric and anionic surfactants for cEOR applications using a novel approach. *Colloids and Surfaces A: Physicochemical and Engineering Aspects* 476: 17-23.
- Karimi A, Fakhroueian Z, Bahramian A, et al. (2012) Wettability alteration in carbonates using zirconium oxide nanofluids: EOR implications. *Energy & Fuels* 26: 1028-1036.
- Lake LW, Johns R, Rossen WR, et al. (2014) Fundamentals of enhanced oil recovery.
- Lu J and Pope GA. (2017) Optimization of gravity-stable surfactant flooding. *SPE Journal* 22: 480-493.
- Mahani H, Menezes R, Berg S, et al. (2017) Insights into the Impact of Temperature on the Wettability Alteration by Low Salinity in Carbonate Rocks. *Energy & Fuels* 31: 7839-7853.
- Masnadi MS, El-Houjeiri HM, Schunack D, et al. (2018) Global carbon intensity of crude oil production. *Science* 361: 851-853.
- Nouqabi RQM, Zargar G, Takassi MA, et al. (2017) Wettability alteration in enhanced oil recovery process using new amphoteric and cationic surfactants. *An International Peer Reviewed Open Access Journal For Rapid Publication*: 704.
- Nwidee LN, Theophilus S, Barifcani A, et al. (2016) EOR processes, opportunities and technological advancements. *Chemical Enhanced Oil Recovery (cEOR)-a Practical Overview*: 2-52.
- Okasha TM, Funk JJ and Rashidi HN. (2007) Fifty Years of Wettability Measurements in the Arab-D Carbonate Reservoir. *SPE Middle East Oil and Gas Show and Conference*. Manama, Bahrain: Society of Petroleum Engineers, 10.
- Patel D, Thakar V, Pandian S, et al. (2019) A review on casing while drilling technology for oil and gas production with well control model and economical analysis. *Petroleum* 5: 1-12.
- Rieger MM. (2017) Surfactant chemistry and classification. *Surfactants in cosmetics*. Routledge, 21-48.
- Seethapalli A, Adibhatla B and Mohanty KK. (2004) Wettability Alteration During Surfactant Flooding of Carbonate Reservoirs. *SPE/DOE Symposium on Improved Oil Recovery*. Tulsa, Oklahoma: Society of Petroleum Engineers, 10.
- Shen L, Zhu J, Liu L, et al. (2017) Flotation of fine kaolinite using dodecylamine chloride/fatty acids mixture as collector. *Powder Technology* 312: 159-165.

- Sivasankar P and Kumar GS. (2018) Modelling the influence of interaction between injection and formation brine salinities on in-situ microbial enhanced oil recovery processes by coupling of multiple-ion exchange transport model with multiphase fluid flow and multi-species reactive transport models. *Journal of Petroleum Science and Engineering* 163: 435-452.
- Standnes DC and Austad T. (2000) Wettability alteration in chalk: 2. Mechanism for wettability alteration from oil-wet to water-wet using surfactants. *Journal of Petroleum Science and Engineering* 28: 123-143.
- Sun L, Wu X, Zhou W, et al. (2018) Technologies of enhancing oil recovery by chemical flooding in Daqing Oilfield, NE China. *Petroleum Exploration and Development* 45: 673-684.
- Szaniawska M, Taraba A and Szymczyk K. (2017) Determination of CMC values of the surfactant solutions. *6th European Young Engineers Conference*. 186.
- Wang J, Wang S, Kang Z, et al. (2017) Interference optimization of surfactant/polymer flooding and surfactant flooding in daqing oilfield. *Electron. J. Geotech. Eng.* 22: 1575-1586.

Tables;

Table 1. Crude oil characteristics in this oilfield

Parameter	Value	Unit
Density of dead oil @ 15°C	0.9513	Kg/L
API Gravity	25	API
Viscosity @ 40 °C	38.51	cSt
Asphaltene content	5.24	% wt
Water Content	0.17	% Volume

Table2. Formation brine components

Brine Type	TDS (mg/L)	pH (25 °C)	pH (85 °C)	Density (25 °C) g/cm ³	Density (85 °C) g/cm ³
KCl	1540	6.6-6.9	6.5-6.8	1-1.0045	0.985-0.99
MgCl ₂	5142	6.8-7.1	6.65-7	0.95-1	0.98-0.985
CaCl ₂	3125	6.7-7.1	6.5-7	1.0002-1.003	0.98-0.985
NaCl	112540	6.21-6.68	6.12-6.53	1-1.0025	0.975-0.98

Crude oil composition is depicted in Table 3.

Table 3. Crude oil Composition

Composition	Mole%	Composition	Mole%

C₁	20.14	C₈	3.42
C₂	6.59	C₉	4.13
C₃	5.14	C₁₀	3.84
nC₄	1.25	C₁₁	3.85
iC₄	2.96	C₁₂₊	2.4
nC₅	1.54	CO₂	0.84
iC₅	2.36	H₂S	0
C₆	4.52	N₂	0.3
C₇	20.14		

Table 4. Core flooding steps

Steps	Procedure
1	Provided core samples dried at the temperature of 70 °C for four days.
2	Permeameter-Porodimeter device was used to measure the porosity and permeability.
3	Core Samples were placed in the core holder and the confining pressure is 2.1Pa.
4	Core samples were vacuumed to remove the air for 24 hours.
5	0.5 mL/min of crude oil was injected to the core holder to reach the water cut to 1%.
6	The water flooding procedure is done with the flow rate of 0.5 mL/min to establish the residual oil saturation.
7	The specified volume of two surfactants were injected to the core samples on the miscible condition at the flow rate of 0.5 mL/min to reach the water cut of 99%. The working pressure for the supercritical carbon dioxide is 1.8 Pa.

Figures;

Figure 1. Schematic of coreflooding experiment

Figure 2. Contact angle for two surfactants

Figure 3. Contact angle measurement for two surfactants.

Figure 4. Interfacial Tension for Two Surfactants

Figure 5. Oil Recovery Factor for different scenarios.