Aberystwyth University

Visualisation of flooding along an unvegetated, ephemeral river using Google Earth Engine

Li, Jiaguang; Tooth, Stephen; Zhang, Kun; Zhao, Yang

Published in:

Journal of Environmental Management

DOI:

[10.1016/j.jenvman.2020.111559](https://doi.org/10.1016/j.jenvman.2020.111559)

Publication date:

2021

Citation for published version (APA):

Li, J., Tooth, S., Zhang, K., & Zhao, Y. (2021). Visualisation of flooding along an unvegetated, ephemeral river using Google Earth Engine: Implications for assessment of channel-floodplain dynamics in a time of rapid environmental change. *Journal of Environmental Management*, 278(Pt 2), [111559].
<https://doi.org/10.1016/j.jenvman.2020.111559>

Document License

CC BY-NC-ND

General rights

Copyright and moral rights for the publications made accessible in the Aberystwyth Research Portal (the Institutional Repository) are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the Aberystwyth Research Portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the Aberystwyth Research Portal

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

tel: +44 1970 62 2400

email: is@aber.ac.uk

**Visualisation of flooding along an unvegetated, ephemeral river using
Google Earth Engine: implications for assessment of channel-floodplain
dynamics in a time of rapid environmental change**

Jiaguang Li^{1*,2}, Stephen Tooth³, Kun Zhang⁴, Yang Zhao¹

1 Key Laboratory of Tectonics and Petroleum Resources of the Ministry of Education, China University of
Geosciences, Wuhan, 430074, China

2 Key Laboratory of Theory and Technology of Petroleum Exploration and Development in Hubei
Province, Wuhan 430074, China

3 Department of Geography and Earth Sciences, Aberystwyth University, Aberystwyth, SY23 3DB, UK

4 Institute of Geological Survey of Qinghai Province, Xining, 810012, China

Correspondence: Key Laboratory of Tectonics and Petroleum Resources of the Ministry of Education,
China University of Geosciences, Wuhan, 430074, China

Tel.: +86 27 67883067 fax: +86 27 67883051

E-mail address: jiaguangli@cug.edu.cn, jiaguangli@gmail.com (J. Li)

Abstract

Given rapid environmental change, the development of new, data-driven, interdisciplinary approaches is essential for improving assessment and management of river systems, especially with respect to flooding. In the world's extensive drylands, difficulties in obtaining field observations of major hydrological events mean that remote sensing techniques are commonly used to map river floods and assess flood impacts. Such techniques, however, are dependent on available cloud-free imagery during or immediately after peak discharge, and single images may omit important flood-related hydrogeomorphological events. Here, we combine multiple Landsat images from Google Earth Engine (GEE) with precipitation datasets and high-resolution (<0.65 m) satellite imagery to visualise flooding and assess the associated channel-floodplain dynamics along a 25 km reach of the unvegetated, ephemeral Río Colorado, Bolivia. After cloud and shadow removal, Landsat surface reflectance data were used to calculate the Modified Normalized Difference Water Index (MNDWI) and map flood extents and patterns. From 2004 through 2016, annual flooding area along the narrow (<30 m), shallow (<1.7 m), fine-grained (dominantly silt/clay) channels was positively correlated ($R^2 = 0.83$) with 2-day maximum precipitation totals. Rapid meander bend migration, bank erosion, and frequent overbank flooding was associated with formation of crevasse channels, splays, and headward-eroding channels, and with avulsion (shifting of flow from one channel to another). These processes demonstrate ongoing, widespread channel-floodplain dynamics despite low stream powers and cohesive sediments. Application of our study approaches to other dryland rivers will help generate comparative data on the controls, rates, patterns and timescales of channel-floodplain dynamics under scenarios of climate change and direct human impacts, with potential implications for improved river management.

Keywords: channel dynamics, flood mapping, floodplain, Google Earth Engine, meandering river, unvegetated channel

41 1. Introduction

42 Despite modest progress in brokering international climate governance frameworks (e.g. Paris
43 Agreement), concern is growing over the likelihood of a global average temperature rise of greater than
44 1.5 °C by the end of the 21st century (IPCC, 2014; Hoegh-Guldberg et al., 2018). Consequently, major
45 changes to weather- and climate-related phenomena are likely to occur within the next few generations,
46 which will pose considerable challenges for the maintenance or enhancement of environmental,
47 economic and social resilience. To meet these challenges, new, data-driven, interdisciplinary
48 approaches to enable improved assessment of environmental system dynamics are urgently needed,
49 particularly where there is potential for application in management contexts.

50

51 Rivers are key environmental systems, playing a crucial role in fluxes and stores of water, sediment and
52 nutrients on local, regional and global scales. In many global regions, however, increased atmospheric
53 warming and various human activities (e.g. land use changes, river damming, flow abstraction) are
54 resulting in profound alterations to the hydrological cycle, including changes to precipitation intensities,
55 river flow variability, and groundwater volumes (Gleeson et al., 2020). Such profound hydrological
56 alterations are commonly manifest in shifts in river flood frequency and magnitude (Woodward et al.,
57 2010), with potential consequences for wider river system structure and function. For instance,
58 within-channel and overbank flooding is a key control on river dynamics, including channel and
59 floodplain stability and the distribution of transported sediment (Nicholas and Walling, 1997; Carroll et al.,
60 2004), and also influences many other aspects of ecosystem service delivery such as riparian
61 biodiversity (Millennium Ecosystem Assessment, 2005). Shifts in flood frequency and magnitude may
62 also pose significant hazards, including by facilitating the spread of water-associated diseases and by
63 impacting on human land use, infrastructure, property, and even life (e.g. Hooke, 2000, 2016; Foody et

al., 2004; Ashley and Ashley, 2008; Woodward et al., 2010; Smith et al., 2013; Heaney et al., 2019).

The positive and negative impacts of flooding can affect perennial, humid or tropical region rivers as well as the more commonly intermittent (seasonal) or ephemeral, dryland rivers but accurate mapping and monitoring of flood extents, flood patterns, and associated channel-floodplain dynamics is challenging (Domeneghetti et al., 2019). The challenges are particularly acute in remote, sparsely populated drylands where channel flow gauges are commonly absent or difficult to maintain, and/or field access is often limited during and immediately after the typically irregular flood events (Tooth, 2013; Heritage et al., 2019).

Owing to the difficulties of obtaining field measurements or observations of large or extreme hydrological events in drylands, particular interest has been turning to the use of remote sensing techniques to visualise flooding extent, flooding patterns, and channel-floodplain dynamics along dryland rivers (e.g. Gumbricht et al., 2004; Ip et al., 2006; Milzow et al., 2009; Rowberry et al., 2011; Li et al., 2014a, b, 2018; Thito et al., 2016; Milan et al., 2018; Heritage et al., 2019). Many previous studies have focused on flood mapping from one or a few satellite images captured during or after floods, but these images may contain limited information due to low spectral and temporal resolution (e.g. acquisition dates of satellite imagery long after peak flood events - Ticehurst et al., 2014). In addition, in some dryland regions, obtaining cloud-free imagery during or immediately following peak flood events is notoriously difficult (e.g. Rowberry et al., 2011; Li et al., 2018), and this problem is compounded when attempting to undertake multiple-year mapping and monitoring. Therefore, visualisations of flood extents and patterns remain particularly poorly developed in many drylands. Here, we investigate possible solutions to this problem by using the Google Earth Engine (GEE) platform. The cloud-based GEE platform provides access to

worldwide Landsat satellite imagery and has proven computationally efficient for processing large volumes of remote sensing data (Gorelick et al., 2017). In particular, GEE enables all available imagery for a given rainy season to be integrated into one composite, thereby maximizing the accuracy of flood mapping. A number of studies have used GEE to compile composite images and undertake time series analyses, including mapping global water body occurrence and dynamics (Pekel et al., 2016) and assessing monthly changes to water body surface areas (Yang et al., 2020a). Other studies have demonstrated how composite images from GEE enable robust flood monitoring and increased accuracy of flood mapping (Clement et al., 2018; Uddin et al., 2019; DeVries et al., 2020).

In this study, we focus on a 25 km long reach of the unvegetated, ephemeral Río Colorado approaching its terminus on the margins of Salar de Uyuni, Bolivia, the world's largest salt lake (Fig. 1). We generate time-series maps (2004 through 2016) of flood extent and flood patterns. We then combine these maps with other datasets (precipitation measurements, higher resolution satellite imagery) to investigate the controls and consequences of flooding over this time period, especially the associated channel-floodplain dynamics. While the value of GEE-based visualisation and quantification of global water bodies and flooding has been amply demonstrated (Pekel et al., 2016; Yang et al., 2002a; Clement et al., 2018; Uddin et al., 2019; DeVries et al., 2020), until now the approach has not been widely applied for detailed flood mapping and associated analyses of channel-floodplain dynamics along unvegetated, ephemeral rivers.

Reaches of the middle and lower Río Colorado, as well as the neighbouring Río Capilla, have been subject to previous hydrological, geomorphological and sedimentological investigations (e.g. Donselaar et al., 2013; Li et al., 2014a, 2014b, 2015, 2018, 2019, 2020, 2021; Li and Bristow, 2015; van

Toorenenburg et al., 2018). Similar to some other dryland river systems worldwide (e.g. Ielpi, 2018; Ielpi and Laptre, 2019), the net moisture deficit and highly saline setting means that these middle and lower reaches are essentially devoid of vegetation cover. Frequent rainfall-flooding events have been shown to be triggers for widespread, pronounced and rapid cascades of channel and floodplain dynamics on (sub-)decadal timescales (e.g. Li et al., 2019, 2020), including meander bend migration and cutoff, crevasse channel and splay formation, and avulsion (defined as the shifting of flow from one channel to another). These previous studies, however, have not generated multi-year flood visualisations or comprehensively investigated the consequences of this flooding for channel-floodplain dynamics.

The specific objectives of this paper thus are to: 1) integrate Landsat data (cloud cover <10%) available for the rainy season of each year from 2004 through 2016 into composite images, and then map flooding extent and pattern using the Modified Normalized Difference Water Index (MNDWI); 2) analyse available precipitation datasets to investigate the relationship between short-term precipitation totals and flooding; 3) use higher resolution satellite imagery to characterize and explain the response of the Ro Colorado channels and floodplain to the flooding; and 4) discuss the wider applicability of these data-driven, remote sensing-based approaches for improving assessment and management of a wider diversity of dryland rivers.

2. Study area

The Ro Colorado catchment is located in the southern Altiplano basin in the central Andes of South America (Fig. 1a-b). The Altiplano basin formed as part of the Andean oceanic-continental convergent margin and is characterized by an overall semiarid climate, with a marked pattern of increasing aridity

133 from north to south owing to the prevailing low pressure weather systems and poleward low-level airflow
134 (Lenters and Cook, 1999).

135

136 The Río Colorado catchment comprises upper Ordovician to Tertiary clastic sedimentary and igneous
137 rocks, with Quaternary sediments widespread (Horton and Decelles, 2001; Marshall et al., 1992). The
138 study area has been tectonically quiescent in the late Pleistocene and Holocene, despite the presence of
139 some prominent fault escarpments in the catchment (Bills et al., 1994; Baucom and Rigsby, 1999;
140 Donselaar et al., 2013; Rigsby et al., 2005). The river flows in a south-north direction, and in the lower
141 reaches develops a fan-shaped form as it approaches its terminus on the southeastern margin of Salar
142 de Uyuni (Fig. 1b). Previous studies have tended to focus on these fan-shaped, lower reaches (e.g.
143 Donselaar et al., 2013; Li et al., 2014a, b, 2015b, 2018; Li and Bristow, 2015; van Toorenenburg et al.,
144 2018) but in this study, the main focus is on a reach of the Río Colorado located 25 to 50 km upstream of
145 the river terminus (Fig. 1c). The distribution of numerous active, abandoning and abandoned channels
146 (Fig. 1c) indicates that this low gradient reach (mean valley gradient ~ 0.000232 m/m – Fig. 1f) has been
147 subject to repeated avulsions over the last few hundred to few thousand years; during an avulsion, flow
148 is diverted from an active channel and erodes a newer channel on the floodplain and/or reoccupies an
149 older channel, processes that lead to gradual abandonment of the originally active channel (Slingerland
150 and Smith, 2004). In the study reach, two main ‘reach-scale’ avulsions have occurred since the 1970s,
151 with reaches A-B initially forming the trunk channel, then reaches C-D, and then reaches C-B (Fig. 1c –
152 see also Li et al., 2020). During this time period, ‘local-scale’ avulsions have also occurred within reach
153 D (Fig. 1d-e). Currently, reach A is abandoned and three principal channels are present (Fig. 1c): the
154 trunk channel (reaches C-B) and two secondary channels (D1, D2). Given the different levels of recent
155 and contemporary activity in these reaches, in this study, we focused mainly on reaches B-D (see Table

1 for a summary of the typical channel and floodplain characteristics). Normalized Difference Vegetation Index (NDVI) analysis (Li et al., 2015a) and field observations demonstrate that the middle and lower reaches of the Río Colorado are essentially unvegetated (Fig. 2).

The study area is influenced by the El Niño-Southern Oscillation (ENSO), with episodic La Niña conditions associated with phases of enhanced rainfall and flooding. Although highly variable, average annual rainfall in the study area is ~185 mm and is greatly exceeded by the annual potential evapotranspiration of 1500 mm. Most precipitation occurs as a consequence of thunderstorms in the rainy season that lasts from December through March (Li et al., 2014a). Daily maximum precipitation totals can represent a significant percentage of the annual total but only rarely exceed 40 mm (Li, 2014; Li and Bristow, 2015). The Río Colorado is ephemeral, and although no formal flow gauging records exist, previous observations indicate that small to moderate (sub-bankfull) river flow events occur one or more times in most years, with larger events (bankfull or above) also occurring in most years (Li et al., 2014a, 2019, 2020).

3. Materials and Methods

The GEE platform provides access to Landsat satellite imagery over the last ~40-50 years but in this study we use the GEE platform to generate annual composite images from the Landsat images acquired within the rainy seasons from 2004 through 2016 (Fig. 3 and SI Fig. 1), a time period for which higher resolution (<0.65 m) images are also available. GEE is accessed and controlled through an internet-accessible application programming interface (API) and an associated web-based interactive development environment (IDE) (Gorelick et al., 2017). Therefore, all the methods of data processing outlined in the following sections were performed through coding.

179

180 **3.1 Materials**

181 We used Landsat 5 and Landsat 8 imagery acquired during the time period of interest (SI Fig. 1; SI Table
182 1). This imagery is available for all years from 2004 through 2016, except for 2012 and 2013. In the
183 study area, no archived Landsat TM images are available from 2012 onwards and no Landsat 8 data
184 exist for the rainy season of 2012-2013 (SI Fig. 1). Daily precipitation data were collected for the period
185 2004 through early 2017 from the Bolivian Servicio Nacional de Meteorología e Hidrología in the Uyuni
186 area (SI Fig. 1). For shorter reaches within the study area, higher resolution imagery (<0.65 m) was
187 acquired from Google Earth Pro™ (SI Table 2).

188

189 **3.2 Methods**

190 3.2.1 Mapping of flooding extent and patterns

191 To extract flooding extents and patterns, the Landsat images acquired in each rainy season (December
192 through March) were integrated and processed on the GEE platform (SI Fig. 2). Landsat surface
193 reflectance data including Thematic Mapper (TM) and Operational Land Imager (OLI) imagery were
194 preprocessed by subsetting into the region of interest (i.e. mainly along the Río Colorado – Fig. 1c).
195 Images with cloud cover of <10% were then selected (SI Table 1) and processed for cloud masking to
196 remove cloud-covered or cloud-shadowed regions. Within the GEE platform, all the Landsat images
197 that met these requirements were compiled in annual collections. As an example, for the 2016 rainy
198 season, four images (acquired on December 30, January 15, February 16, and March 3) are available
199 and contained in the annual collection (SI Fig. 3). Modified Normalized Difference Water Index (MNDWI)
200 is widely used to extract wet land ('water bodies') due to stronger absorption by water of solar radiation
201 in shortwave infrared (SWIR) bands than in near infrared (NIR) and visible bands (Xu, 2006):

$$MNDWI = \frac{\rho_{green} - \rho_{SWIR}}{\rho_{green} + \rho_{SWIR}} \quad (1)$$

where for Landsat TM data, ρ_{green} is reflectance in Band 2 and ρ_{SWIR} is reflectance in Band 5, and for Landsat 8 data, ρ_{green} is reflectance in Band 3 and ρ_{SWIR} is reflectance in Band 6. MNDWI mapping results in an image with values between 1 and -1, whereby pixels with high inundation probability have a high (positive) MNDWI. To map the maximum flooding extent, we made wettest-pixel composites from images in the annual collections. The pixel is considered 'inundation active' when wet land appears in any one image. As such, the annual time-series composite images are generated based on the pixel that contains the maximum MNDWI value from the annual collection (SI Fig. 3).

The imaging of water indices shows a polarisation trend whereby the pixel values of wet land return positively large values, whereas those of other objects tend to be theoretically negative. Thus, the image histogram is characterised by a smoothed, two-peaked representation of the distribution of foreground and background pixels. Histogram shape-based Otsu's method has proven useful for defining the optimal segmentation threshold in the water index image (Yang and Chen, 2017; Yang et al., 2017, 2018, 2020a, 2020b; Li et al., 2018). Thus, the time-series composite images with the wettest pixels were employed to generate the flooding maps (SI Fig. 4) using Otsu's method (Otsu, 1979). Otsu's method was used to determine dynamic thresholds of classification while visual interpretation of flooded areas along with 50 random referenced points (Fig. 1c) was used to examine the classification accuracy. Single pixels were classified as flooded areas if the MNDWI was greater than its threshold value in the time-series composite image. Confusion matrices were used to assess the methods in this study. Using a confusion matrix, pixels in the study area were divided into four classes including TP (true positive), FN (false negative), FP (false positive), and TN (true negative). These four classes represent accurate pixel extraction (TP), missing water bodies (FN), inaccurate extraction (FP), and the accurate

225 rejection (TN) of non-water, respectively. Subsequently, four normalized metrics including producer's
226 accuracy (PA), user's accuracy (UA), overall accuracy, and kappa coefficient were used to assess the
227 performance of the methods. PA indicates completeness, meaning that a low PA indicates high
228 omission error. UA shows correctness, meaning that a low UA indicates an extreme commission error.
229 Following these analyses, flooded land ('wet land'/'water bodies') was mapped and exported as
230 polygons, and areas were calculated using ArcGIS.

231

232 3.2.2 Analysis of precipitation data

233 Daily precipitation data in the study area were processed and extracted to derive 2-day precipitation and
234 3-day precipitation datasets. From these datasets, yearly daily maximum precipitation, 2-day maximum
235 precipitation and 3-day maximum precipitation were obtained. Rate of change was calculated as the
236 difference between two temporally adjacent values of maximum precipitation, divided by the length of
237 time between the two observation points. These datasets then provided the basis for investigation of
238 the relationships with flooding extent and pattern.

239

240 3.2.3 Investigation of channel-floodplain morphodynamics

241 The high resolution (<0.65 m) satellite imagery (SI Table 2) was used to document and quantify the
242 impact of flooding on channel bank erosion and channel-floodplain morphology. Only imagery for 2004
243 and 2018 covers the whole study reach but six scenes (2004, 2007, 2010, 2013, 2016 and 2018) cover
244 part of the downstream reaches (see boxed area labelled 'downstream reaches' in Fig. 3a). A total of
245 52 bends along the trunk channel (reaches C-B, $n = 33$) and a secondary channel (D1, $n = 19$) were
246 analysed for various parameters including channel sinuosity (defined as channel distance/straight-line
247 distance), lateral migration rates, and erosional and depositional areas (Fig. 3a). The small number of

bends ($n = 4$) along the shorter channel D2 were not analysed. For analysis, newer high-resolution images were registered to the reference image of 2004 using the remote sensing image analysis software ENVI 5.3. Following standard procedure, the migration distances for single bends between two observation dates were measured at the outer bank. The lateral migration rates were then calculated as the ratio of the migration distance to the length of time between the observation dates. Areas of active erosion and deposition were mapped and exported as polygons, and areas were calculated using ArcGIS. Across all the active, abandoning and abandoned channels, select reaches were also investigated for other evidence of channel-floodplain morphological dynamics (e.g. Fig. 3b-c).

256

4. Results

4.1 Accuracy assessment

An accuracy threshold plays an important role in differentiating flooded areas (i.e. wet land/water bodies) from dry land areas. During the time period of interest, the average threshold value by Otsu's method is -0.22 (maximum of -0.135, minimum of -0.254) (SI Fig. 5). Between 2004 and 2007, the values fluctuate from -0.212 to -0.135 but between 2008 and 2016 threshold values are more stable at ~ -0.25 .

263

For the time period 2004 through 2016, the mean producer's accuracy is 91.68% (minimum of 79.31%), the mean user's accuracy is 97.33% (minimum of 92.86%) and the mean overall accuracy is 93.09% (minimum of 86.00%) (Table 2). The mean kappa coefficient is 0.84 (Table 2). Although the active trunk channel (width < 30 m) can be extracted, the main errors in separation of flooded areas and dry land areas occurred in the water-land transition zone near river channel banks. Overall, the results suggest that the Landsat composite-derived MNDWI can be used for detecting flooded areas in the study with a high level of accuracy.

271

272 **4.2 Flooding extent and pattern in relation to channel-floodplain topography**

273 Mapping shows that during the time period of interest, flooding area averaged 35.8 km² (Figs 4 and 5a).
 274 Maximum flooding extent occurred in 2006 (up to 48 km²) while minimum flooding extent occurred in
 275 2011 (14 km²) (Figs 4 and 5a). In many years, flooding is especially prominent to the west of the trunk
 276 channel (active reaches C-B and in the area of abandoned channel A) and around the downstream
 277 reaches of the secondary channels D1 and D2 (Fig. 4). Although some flooding might result from direct
 278 precipitation and consequent ponding on the floodplain, overbank flow emanating from the trunk and
 279 secondary channels clearly also makes a contribution. Along the trunk channel (reach C), the linear
 280 nature (narrow, elongated pattern) of some flooded areas demonstrates that at least some floodwater
 281 flows through meander cutoffs and remnant depressions created by older, largely abandoned channels
 282 on the western side of the floodplain (see Fig. 1c) before returning to the trunk channel (reach B) farther
 283 downstream (for the clearest examples, see years 2007 and 2009 in Fig. 4).

284

285 **4.3 Flooding and precipitation**

286 As expected, across the time period of interest, flooding area shows a strong positive correlation with the
 287 different precipitation datasets (Fig. 5a). The correlation between rate of change in flooded area and in
 288 2-day maximum precipitation is slightly stronger ($R^2 \sim 0.83$) than for daily maximum precipitation ($R^2 \sim$
 289 0.74) and 3-day maximum precipitation ($R^2 \sim 0.77$) (Fig. 5b). Although the time period of interest is
 290 relatively short (2004 through 2016), and so caution needs to be exercised, the changes in maximum
 291 precipitation appear to be broadly in agreement with ENSO dynamics, as reflected in the Multivariate
 292 ENSO Index (MEI)(Fig. 5c). Low to negative MEI values indicate La Niña periods and tend to be
 293 associated with high maximum precipitation totals and flooded areas (e.g. 2006, 2008), while higher MEI

values indicate El Niño periods and tend to be associated with lower maximum precipitation totals and flooded areas (e.g. 2009, 2015) (Fig. 5c). Clearly, however, longer term datasets will be needed to undertake more robust statistical analyses to establish the degree of correspondence between ENSO, rainfall and flooding.

4.4 Channel-floodplain morphodynamics

Analysis of 52 meander bends along the trunk channel (reaches C-B) and secondary channel D1 (Fig. 3a) reveals that many bends are laterally migrating (e.g. Fig. 3b-c) at rates ranging up to 8 m/yr. Lateral migration involves both erosion and deposition (Fig. 3b-c); from an aerial (plan view) perspective, erosion is occurring over an area of $2.245 \times 10^5 \text{ m}^2$ (0.2245 km^2) and deposition over an area of $1.518 \times 10^5 \text{ m}^2$ (0.1548 km^2). The majority of bends are experiencing more erosion than deposition (SI Fig. 6a and c). Along both reaches C-B and D1, the majority of bends have increased in sinuosity between 2004 and 2018 (SI Fig. 6b and d), leading to increased sinuosity along the channels as a whole.

Channel D1 is currently undergoing gradual abandonment, with flow increasingly shifting to the trunk channel (reach B) in the middle of the study reach (Fig. 1c) as well as to secondary channel D2 farther downvalley (Fig. 1d). The ongoing impacts of this unfolding avulsion are captured by the higher resolution images (Fig. 6). Channel D2 was already present in 2004 but in subsequent years (2007, 2010) widened significantly, and by 2013 was clearly the dominant channel (Fig. 6a-d). Over the same time period, D1 decreased in width (Fig. 6a-d). Flow shifting has been accompanied by significant channel-floodplain topographic development, including levee breaching and crevasse splay formation and extension (Fig. 6b-c). Particularly dense networks of crevasse splays have developed around the channel D1 bend downstream of the avulsion node (Fig. 6b-c), which may be related to sediment infilling

317 along this abandoning bend and associated flow displacement overbank. Farther downstream along
318 channel D2, an additional short reach has also been subject to avulsion (Fig. 1d), with flow increasing
319 shifting from an easterly to a more westerly channel (Fig. 1e). Along this short reach, levee breaching
320 and crevasse splay formation is not yet evident.

321

322 **5. Interpretation**

323 GEE-based flood visualisation has revealed areas of prominent flooding in the study area, including
324 adjacent to the trunk channel (reaches C-B) and the more downstream reaches of secondary channels
325 D1 and D2 (Fig. 4). At the scale of the study reach, this flooding pattern demonstrates the high degree
326 of channel-floodplain connectivity and further illustrates how complex spatial patterns of water flow on
327 floodplains pose a challenge for hydraulic modelling approaches (c.f. Bridge, 2003). Annual flooding
328 correlated most strongly ($R^2 = 0.83$) with 2-day maximum precipitation totals (Fig. 5b). This illustrates
329 the importance of considering consecutive days' precipitation when analysing flooding patterns, and
330 provides a counterbalance to the previous emphases on the influence of short-duration (<1 day)
331 precipitation events on flooding and channel-floodplain dynamics along small, arid-zone, ephemeral
332 rivers (e.g. Schick, 1988; Dick et al., 1997; Reid and Frostick, 2011). Although caution needs to be
333 exercised, the tendency for higher precipitation totals and flooding extent to be associated with a low or
334 negative MEI (Fig. 5c) supports allied research in the study area that has revealed how short-term
335 (yearly to decadal) clusters of chute cutoffs on meander bends are closely related to La Niña-driven flood
336 events (Li et al., 2020).

337

338 Along with chute cutoff formation (Li et al., 2020), significant bend migration, levee breaching, crevasse
339 splay development, and avulsion has occurred in the study reach during the last couple of decades (Figs

1d-e, 3, 6). The satellite images of the study reach show numerous older, sinuous channels to the west of the current trunk channel (Fig. 1c), suggesting that these avulsion dynamics have been a natural part of longer term (likely centennial to millennial) river system responses. The high degree of channel-floodplain connectivity and rapid (decadal-scale) avulsion dynamics that are so characteristic of this river system enable the sites of potential future avulsions to be identified. For instance, in the upstream reach of the trunk channel (reach C), a headward eroding channel has extended between 2004 and 2018 and is now connected with crevasse channels on an outer meander bend (Fig. 3b-c). During high flows, these crevasse channels will convey flow to the headward eroding channel, likely leading to channel incision and widening, and increasing flow diversion to this newly eroded channel. In turn, this may lead to gradual abandonment of the trunk channel in the reach immediately downstream.

Significantly, however, the evidence from channel D1 shows that flow diversion does not necessarily lead to cessation of meander bend migration in reaches immediately downstream, at least not in the early stages of channel abandonment. Two main avulsion nodes are present along channel D1, with flow diversion to the trunk channel (reach B) taking place in the middle of the study area (Fig. 1c) and flow diversion to secondary channel D2 taking place farther downstream (Fig. 1d). Increasing flow diversion from channel D1 to trunk channel reach B and to D2 has occurred post-2004 (Fig. 6) but many individual bends along D1 nonetheless still experienced significant erosion and became increasingly sinuous between 2004 and 2018 (SI Fig. 6c-d). These findings demonstrate that in this unvegetated, ephemeral river, which is characterised by shallow channels that experience frequent within-channel and overbank flooding, dynamic adjustment of bends can continue to take place even in the early stages of channel abandonment.

363

364 Along the active and abandoning channels of the Río Colorado, the ongoing bend adjustments and other
365 channel-floodplain dynamics (e.g. levee breaching and crevasse splay development) are associated
366 with significant erosion (SI Fig. 6a and c). As a consequence, and despite some counterbalancing
367 deposition in point bars, on levees and in splay channels, sediment is exported from the study area to
368 the reaches farther downstream towards the river terminus. In these fan-shaped lower reaches,
369 deposition is more widespread, with progradation of channel-belt sediments occurring across older
370 (pre-late Holocene) lacustrine sediments that are related to a formerly more extensive Salar de Uyuni
371 (Donselaar et al., 2013; Li and Bristow, 2015; Li et al., 2019).

372

373 **6. Discussion**

374 This study has used a combination of GEE-based flood visualization, secondary datasets, and higher
375 resolution satellite imagery, complementing other recent research that has used various remote sensing
376 approaches to investigate river forms, processes and responses (for overviews, see Carbonneau and
377 Piégay, 2012; Gilvear and Bryant, 2016; Gilvear et al., 2016; Entwistle et al., 2018; Tomsett and Leyland,
378 2019; Piégay et al., 2020). Similar approaches to those used in our study could be applied to many
379 other rivers globally, but given the difficulties of field observations of flooding and flood impacts in remote
380 drylands, the application to a wider range of dryland rivers may be particularly useful, as discussed in the
381 sections below.

382

383 **6.1 Wider application of the study approaches**

384 Many previous studies of flood extent, pattern and impact in dryland rivers have relied on single satellite
385 images, despite concerns over high cloud coverage and the known limitations of acquiring images after

peak flow has taken place (e.g. Chignell et al., 2015; Li et al., 2018). The generation of Landsat-derived composites using the GEE platform, however, enables analysis of multi-day imagery for a given rainy season, thereby ensuring that all satellite imagery with suitably low cloud cover can be used to increase the accuracy of flood mapping. More accurate mapping is particularly important for those dryland rivers that are characterized by downstream reductions in cross-sectional area, for prominent overbank flooding and marked channel-floodplain dynamics may occur even during moderate floods. Besides the lower Río Colorado (Li et al., 2014a, 2019; Li and Bristow, 2015), examples include various rivers in the Australian and South African drylands (Tooth, 1999, 2000; Tooth et al., 2002, 2014; Ralph and Hesse, 2010; Larkin et al., 2017a, 2020a). Our study approaches could also be applied to other non- or poorly-vegetated, ephemeral rivers such as characterise parts of the southwest USA (Ielpi, 2018; Ielpi and Lapôtre, 2019), or to those dryland rivers where riparian vegetation density and/or health is declining owing to climate change or direct human interventions that have resulted in desiccation, salinisation, pollution, increased fire frequency, or disease (e.g. Stromsoe and Callow, 2012; Jaeger et al., 2017).

400

401 **6.2 Comparing channel-floodplain dynamics in unvegetated and vegetated dryland rivers**

While a substantial body of previous research has focused on flood-related, channel-floodplain dynamics in perennial humid or tropical region rivers (e.g. Parker, 2000; Terry et al., 2002; Schanze et al., 2006; Woodward et al., 2010; Wohl et al., 2012), some research attention has also been directed towards studies of flood impacts in intermittent or ephemeral, dryland rivers (for a summary, see Tooth, 2013). In particular, the dynamics of sparsely-vegetated or non-vegetated, ephemeral dryland rivers have been subject to increasing analysis (e.g. Billi et al., 2018; Ielpi, 2018; Ielpi et al., 2018; Ielpi and Lapôtre, 2019) in part because of increasing recognition that some ephemeral dryland rivers may be

highly sensitive systems, whereby sensitivity is defined either in terms of the high propensity for flood-related channel-floodplain dynamics and/or the limited ability to recover from those dynamics (Tooth, 2013; see also Lisenby et al., 2019). Importantly, the high sensitivity of some poorly or non-vegetated, ephemeral dryland rivers can be exploited to provide insight into the longer-term dynamics of more slowly developing dryland rivers. For instance, along with previous studies of the middle and lower Río Colorado and neighbouring Río Capilla, the results of this study show how this system can serve as a large scale natural experiment, with regular La Niña-driven floods driving cascades of channel-floodplain dynamics on (sub-)decadal timescales (cf. Li et al., 2019, 2020), despite low stream powers and cohesive channel perimeter sediments (Table 1). In other disciplines, studies have suggested that the large-scale meteorological shifts associated with ENSO may presage the effects of 21st century regional to global climate change (e.g. Heaney et al., 2019), so these rapid cascades may provide into potential channel-floodplain dynamics in the coming decades. Additionally, the rapid cascades along the Río Colorado provide opportunities to monitor and characterise channel-floodplain dynamics in ways not possible in more vegetated dryland rivers, such as those in Australia and South Africa where otherwise comparable dynamics such as crevasse splay formation, avulsions and headward channel migration have been shown to take place over multidecadal, centennial or longer timescales (e.g. Tooth, 2005; Tooth et al., 2007, 2009, 2014; Larkin et al., 2017b). Along these Australian and South African dryland rivers, unit stream powers during floods tend to be similar to the Río Colorado ($<10 \text{ W/m}^2$) and while channel bed sediments may be coarser (sand, minor gravel), channel bank and floodplain sediments also tend to be cohesive (e.g. dominantly clay and silt). This suggests that while the basic patterns and trajectories of the channel-floodplain dynamics may be similar, the slower rates in these other dryland rivers can be attributed to the additional hydraulic roughness and resistance to erosion provided by the riparian vegetation (e.g. grasses and sedges, or grasses and

shrubs/trees).

6.3 Implications for dryland river and flood management

Previous studies of dryland rivers have demonstrated how different data-driven, interdisciplinary approaches can play a vital part in improving assessment of channel-floodplain dynamics, with implications for management. In some instances, remote sensing approaches have formed a key component of these study approaches. For instance, Tooth et al. (2014) used a combination of field investigations, geochronology (luminescence dating), and remote sensing (mainly aerial image and orthophotograph interpretations) to reconstruct the historical and longer term (multi-centennial) dynamics of the Blood River floodplain wetlands in dryland South Africa. These reconstructions provided a reference condition against which to assess recent (decadal-scale) channel-floodplain dynamics. Prior to the early part of the last century, the wetlands were characterised by a through-going, meandering channel but over the last 70-80 years, major morphological and sedimentary changes have occurred in the upper part of the wetlands. The former meandering channel has been replaced by a straighter channel that decreases in size downstream and now terminates in a unchannelled reedbed, creating a major discontinuity in downvalley water and sediment transfer that is likely to persist for centuries (Tooth et al., 2014). Along the Blood River, the initial cause(s) of these profound channel-floodplain dynamics are not known but may be related to a period of severely decreased flow in the 1930s and/or anthropogenic impacts (e.g. river damming) (Tooth et al., 2014).

Even in study settings where geochronological constraints on longer term channel-floodplain dynamics are absent and/or remote sensing datasets have a more restricted temporal range, remote sensing image analysis can still help to characterise past river responses and so provide context for assessment

455 of the significance of channel-floodplain dynamics on more recent timescales (e.g. decades). For
456 instance, along the study reach of the Río Colorado, satellite imagery reveals numerous older, sinuous
457 channels to the west of the current trunk channel (Fig. 1c). This evidence suggests that the avulsion
458 dynamics that have characterised parts of the study reach over the last few decades (see also Li et al.,
459 2020) are a natural part of longer term (likely centennial to millennial) river system responses, and are
460 not the result of recent climate change or other human activities in the catchment. In other words, and
461 in stark contrast to the Blood River example where an historically unprecedented channel-floodplain
462 transformation has occurred, the recent dynamics along the Río Colorado are simply part of the
463 expected (i.e. normal) range of longer term, river responses.

464

465 The contrast between the recent dynamics of the Blood River and Río Colorado is worth stressing as it
466 illustrates an important point with potential significance for dryland river and flood management.
467 Brierley and Fryirs (2005) make a clear distinction between river behaviour (adjustments to
468 channel-floodplain morphology that help to maintain a characteristic morphology and set of process
469 attributes) and river change (a fundamental shift in morphology and process associations that indicate
470 reach evolution to a different river type). River behaviour (e.g. Río Colorado) and river change (e.g.
471 Blood River) thus may pose different management challenges that require different strategies to cope
472 with the attendant alterations to flood extent and flood patterns. In cases of river behaviour, one
473 management strategy may simply be to accommodate the expected range of channel-floodplain
474 adjustments (e.g. through floodplain land use re-zoning), whereas in cases of river change, more
475 proactive management approaches may be needed (e.g. using structural interventions). During
476 forthcoming decades, it will be particularly important to identify and characterise thresholds of dryland
477 river change (Tooth, 2018; Larkin et al., 2020a, b), especially in cases where altered flooding extent and

patterns will threaten ecosystem service delivery (e.g. McCarthy et al., 2010), facilitate the spread of water-associated diseases (e.g. Malan et al., 2009; Smith et al., 2013; Heaney et al., 2019), and/or pose a greater hazard for land use, infrastructure, property and life (e.g. Ashley and Ashley, 2008; Woodward et al., 2010). In a time of rapid environmental change, when dryland rivers globally are responding to climate changes and/or other human activities, new data-driven, interdisciplinary approaches will be needed to help determine this distinction between river behaviour and river change, and also to evaluate the appropriate river and flood management strategies.

7. Conclusions

This study has shown how the GEE platform has helped with the visualisation of flooding extent and patterns along an unvegetated, ephemeral river system, and how analysis and quantification of the floods can be combined with other datasets (precipitation, higher resolution imagery) to provide insights into channel-floodplain dynamics on recent, observable timescales. The findings from the Río Colorado improve our understanding of the dynamics of this river in particular, but also provide scope for comparison with the channel-floodplain dynamics of a wider range of dryland rivers in different physiographic contexts, including those with different levels of riparian vegetation.

Of particular value in future research will be additional datasets on short-term (yearly to decadal scale) patterns, rates and timescales of dryland river dynamics, particularly where this improves our ability to distinguish between river behaviour involving channel-floodplain adjustments that remain within the expected range, and river change involving more profound, threshold-based, channel-floodplain changes. Given the strong links between dryland channel-floodplain dynamics, water-associated infectious diseases, and many other aspects of catchment ecosystem service delivery and hazard

501 assessment (Millennium Ecosystem Assessment, 2005), clear potential exists for further data-driven,
502 interdisciplinary studies. In a time of rapid environmental changes, one increasingly defined by
503 humanity's direct and indirect impacts on the Earth system, development of more remote sensing-based
504 approaches should form an essential part of these interdisciplinary studies. This will help to improve
505 visualisation of flooding and associated channel-floodplain dynamics, so providing a key underpinning
506 for dryland river management policy and practice.

507

508 **Acknowledgements**

509 This research was supported by: the National Natural Science Foundation of China (No. 41972114, No.
510 41602121); the Wuhan Applied Foundational Frontier Project (No. 2020020601012281); the
511 Fundamental Research Funds for the Central Universities, China University of Geosciences (Wuhan)
512 (No. CUG150616); and Open Fund (TPR-2017-01) of Key Laboratory (Ministry of Education) of
513 Tectonics and Petroleum Resources (China University of Geosciences, Wuhan, China). J.L. thanks
514 colleagues Oswaldo Eduardo Ramos Ramos, Rafael Cortez, and students Edson Wilder Ramos
515 Mendoza, Wilhelm Alex Mendizabal Cuevas, Samir Nikolar Pacheco, Erick Marcelo Cabero Caballero,
516 Julian Franz Cortez Garvizu (all from Universidad Mayor de San Andrés) for the fieldwork arrangements
517 and assistance near Salar de Uyuni in Bolivia. JL thanks German Aerospace Center for the TanDEM-X
518 data (Grant no. GEOL2320).

519

References

- Ashley, S.T., Ashley, W.S. (2008). Flood fatalities in the United States. *J. Appl. Meteorol. Climatol.*, 47, 805–818. <https://doi.org/10.1175/2007JAMC1611.1>
- Baucom, P.C., Rigsby, C. A. (1999). Climate and lake-level history of the northern Altiplano, Bolivia, as recorded in Holocene sediments of the Rio Desaguadero. *J. Sediment. Res.*, 69, 597–611. <https://doi.org/10.2110/jsr.69.597>
- Billi, P., Demissie, B., Nyssen, J., Moges, G., Fazzini, M., (2018). Meander hydromorphology of ephemeral streams: similarities and differences with perennial rivers. *Geomorphology* 319, 35–46.
- Bills, B.G., de Silva, S.L., Currey, D.R., Emenger, R.S., Lillquist, K.D., Donnellan, A., Worden, B. (1994). Hydro-isostatic deflection and tectonic tilting in the central Andes: Initial results of a GPS survey of Lake Minchin shorelines. *Geophys. Res. Lett.*, 21, 293–296. <https://doi.org/10.1029/93GL03544>
- Bridge, J.S. (2003). *Rivers and Floodplains: Forms, Processes and the Sedimentary Record*, Blackwell, 491 pp.
- Brierley, G.J., Fryirs, K.A. (2005). *Geomorphology and River Management: Applications of the River Styles Framework*. Wiley-Blackwell, 416 pp.
- Carbonneau, P.E., Piégay, H. (2012). *Fluvial Remote Sensing for River Science and Management*. Wiley.
- Carroll, R.W.H., Warwick, J.J., James, A.I., Miller, J.R. (2004). Modeling erosion and overbank deposition during extreme flood conditions on the Carson River, Nevada. *J. Hydrol.* 297, 1–21. <https://doi.org/10.1016/j.jhydrol.2004.04.012>
- Chignell, S.M., Anderson, R.S., Evangelista, P.H., Laituri, M.J., Merritt, D.M. (2015). Multi-temporal independent component analysis and Landsat 8 for delineating maximum extent of the 2013 Colorado Front Range flood. *Remote Sens.*, 7, 9822–9843. <https://doi.org/10.3390/rs70809822>
- Clement, M. A., Kilsby, C. G., Moore, P. (2018). Multi-temporal synthetic aperture radar flood mapping

- 544 using change detection. *Journal of Flood Risk Management*, 11(2), 152–168.
 545 <https://doi.org/10.1111/jfr3.12303>
- 546 DeVries, B., Huang, C., Armston, J., Huang, W., Jones, J. W., Lang, M. W. (2020). Rapid and robust
 547 monitoring of flood events using Sentinel-1 and Landsat data on the Google Earth Engine. *Remote*
 548 *Sensing of Environment*, 240, 111664. <https://doi.org/10.1016/j.rse.2020.111664>
- 549 Dick, G.S., Anderson, R.S., Sampson, D.E. (1997). Controls on flash flood magnitude and hydrograph
 550 shape, Upper Blue Hills badlands, Utah. *Geology*, 25, 45–48.
 551 [https://doi.org/10.1130/0091-7613\(1997\)025<0045:COFFMA>2.3.CO;2](https://doi.org/10.1130/0091-7613(1997)025<0045:COFFMA>2.3.CO;2)
- 552 Domeneghetti, A., Schumann, G.J.P., Tarpanelli, A. (2019). Preface: Remote sensing for flood mapping
 553 and monitoring of flood dynamics. *Remote Sens.*, 11, 11–14. <https://doi.org/10.3390/rs11080940>
- 554 Donselaar, M.E., Gozalo, M.C.C., Moyano, S. (2013). Avulsion processes at the terminus of low-gradient
 555 semi-arid fluvial systems: Lessons from the Río Colorado, Altiplano endorheic basin, Bolivia.
 556 *Sediment. Geol.*, 283, 1–14. <https://doi.org/10.1016/j.sedgeo.2012.10.007>
- 557 Entwistle N, Heritage G, Milan D. (2018). Recent remote sensing applications for hydro and
 558 morphodynamic monitoring and modelling. *Earth Surface Processes and Landforms*, 43, 2283–2291.
- 559 Foody, G.M., Ghoneim, E.M., Arnell, N.W. (2004). Predicting locations sensitive to flash flooding in an
 560 arid environment. *J. Hydrol.*, 292, 48–58. <https://doi.org/10.1016/j.jhydrol.2003.12.045>
- 561 Gilvear, D, Bryant, R. (2016). Analysis of remotely sensed data for fluvial geomorphology and river
 562 science. In Kondolf GM, Piégay H (eds), *Tools in Fluvial Geomorphology*, 2nd edn. Wiley: Chichester,
 563 UK; 103–132.
- 564 Gilvear, D.J., Hunter, P., Stewardson, M., Greenwood, M.T., Thoms, M.C., Wood, P.J. (2016). Remote
 565 sensing: mapping natural and managed river corridors from the micro to the network scale. In Gilvear,
 566 D.J., Greenwood, M.T., Thoms, M.C., Wood, P.J. (eds). *River Science: Research and Management*

- 567 for the 21st Century, Wiley: Chichester, UK; 171–196.
- 568 Gleeson, T. Wang-Erlandsson, L., Porkka, M., Zipper, S.C., Jaramillo, F., Gerten, D., Fetzer, I., Cornell,
569 S.E., Piemontese, L., Gordon, L.J., Rockström, J., Oki, T., Sivapalan, M., Wada, Y., Brauman, K.A.,
570 Flörke, M., Bierkens, M.F.P., Lehner, B., Keys, P., Kummu, M., Wagener, T., Dadson, S., Troy, T.J.,
571 Steffen, W., Falkenmark, M., Famiglietti, J.S. (2020). Illuminating water cycle modifications and Earth
572 System resilience in the Anthropocene. *Water Resources Research*, 56, e2019WR024957.
- 573 Gorelick, N., Hancher, M., Dixon, M., Ilyushchenko, S., Thau, D., Moore, R. (2017). Google Earth Engine:
574 Planetary-scale geospatial analysis for everyone. *Remote Sens. Environ.*, 202, 18–27.
575 <https://doi.org/10.1016/j.rse.2017.06.031>
- 576 Gumbrecht, T., Wolski, P., Frost, P., McCarthy, T.S. (2004). Forecasting the spatial extent of the annual
577 flood in the Okavango delta, Botswana. *J. Hydrol.*, 290, 178–191.
- 578 Heaney, A.K., Shaman, J. and Alexander, K.A. (2019). El Niño-Southern oscillation and under-5 diarrhea
579 in Botswana. *Nature Communications*, 10, 5798.
- 580 Heritage, G., Entwistle, N., Milan, D., Tooth, S. (2019). Quantifying and contextualising cyclone-driven,
581 extreme flood magnitudes in bedrock-influenced dryland rivers. *Adv. Water Resour.*, 123, 145–159.
582 <https://doi.org/S0309170818303828>
- 583 Hoegh-Guldberg, O., Jacob, D., Taylor, M., Bindi, M., Brown, S., Camilloni, I., Diedhiou, A., Djalante, R.,
584 Ebi, K.L., Engelbrecht, F., Guiot, J., Hijikata, Y., Mehrotra, S., Payne, A., Seneviratne, S.I., Thomas, A.,
585 Warren, R. and Zhou, G. (2018). Impacts of 1.5°C global warming on natural and human systems. In:
586 Masson-Delmotte, V., Zhai, P., Pörtner, H.-O., Roberts, D., Skea, J., Shukla, P.R., Pirani, A.,
587 Moufouma-Okia, W., Péan, C., Pidcock, R., Connors, S., Matthews, J.B.R., Chen, Y., Zhou, X.,
588 Gomis, M.I., Lonnoy, E., Maycock, T., Tignor, M. and Waterfield T. (eds.). *Global Warming of 1.5°C.*
589 *An IPCC Special Report on the Impacts of Global Warming of 1.5°C above pre-industrial levels and*

related global greenhouse gas emission pathways, in the context of strengthening the global response to the threat of climate change, sustainable development, and efforts to eradicate poverty. IPCC.

Hooke, J.M. (2000). Geomorphological impacts of a flood event on ephemeral channels in SE Spain. *Geomorphology*, 34, 163–180. <https://doi.org/10.1016/j.geomorph.2016.03.021>

Hooke, J.M. (2016). Geomorphological impacts of an extreme flood in SE Spain. *Geomorphology*, 263, 19–38. <https://doi.org/10.1016/j.geomorph.2016.03.021>

Horton, B.K., Decelles, P.G. (2001). Modern and ancient fluvial megafans in the foreland basin system of the central Andes, southern Bolivia: implications for drainage network evolution in fold - thrust belts. *Basin Res.*, 13, 43–63.

Ielpi, A. (2018). Morphodynamics of meandering streams devoid of plant life: Amargosa River, Death Valley, California. *GSA Bull.*, 131, 782–802. <https://doi.org/10.1130/B31960.1>

Ielpi A, Fralick P, Ventra D, Ghinassi M, Lebeau L, Marconato A, Meek R, Rainbird RH. (2018). Fluvial floodplains prior to greening of the continents: stratigraphic record, geodynamic setting, and modern analogues. *Sedimentary Geology*, 372, 140–172.

Ielpi, A., Lapôtre, M.G.A. (2019). Barren meandering streams in the Modern Toiyabe Basin of Nevada, U.S.A., and their relevance to the study of the pre-vegetation rock record. *J. Sediment. Res.*, 89, 399–415. <https://doi.org/10.2110/jsr.2019.25>

Ip, F., Dohm, J.M., Baker, V.R., Doggett, T., Davies, A.G., Castaño, R., Chien, S., Cichy, B., Greeley, R., Sherwood, R., Tran, D., Rabideau, G. (2006). Flood detection and monitoring with the Autonomous Sciencecraft Experiment onboard EO-1. *Remote Sens. Environ.*, 101, 463–481.

IPCC (2014). Climate Change 2014: Synthesis Report. Contribution of Working Groups I, II and III to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change, IPCC.

- 613 Jaeger, K.L., Sutfin, N.A., Tooth, S., Michaelides, K., Singer, M. (2017). Geomorphology and sediment
614 regimes of intermittent rivers and ephemeral streams. In: Datry, T., Bonada, N. and Boulton, A. (eds),
615 Intermittent Rivers and Ephemeral Streams: Ecology and Management. London: Academic Press,
616 Elsevier, pp.21-49.
- 617 Larkin, Z.T., Tooth, S., Ralph, T.J., Duller, G.A.T., McCarthy, T., Keen-Zebert, A., Humphries, M.S.
618 (2017a). Timescales, mechanisms, and controls of incisional avulsions in floodplain wetlands:
619 Insights from the Tshwane River, semiarid South Africa. *Geomorphology*, 283, 158–172.
620 <https://doi.org/10.1016/j.geomorph.2017.01.021>
- 621 Larkin, Z.T., Ralph, T.J., Tooth, S., McCarthy, T.S. (2017b). The interplay between extrinsic and intrinsic
622 controls in determining floodplain wetland characteristics in the South African drylands. *Earth Surf.*
623 *Process. Landforms*, 42, 1092–1109.
- 624 Larkin, Z.T., Ralph, T.J., Tooth, S., Duller, G.A.T. (2020a). A shifting ‘river of sand’: the profound response
625 of Australia’s Warrego River to Holocene hydroclimatic change. *Geomorphology*, 370, 107385.
- 626 Larkin, Z.T., Ralph, T.J., Tooth, S., Fryirs, K.A., Carthey, A.J.R. (2020b). Identifying threshold responses
627 of Australian dryland rivers to future global hydroclimatic change. *Scientific Reports*, 10, article no.
628 6653.
- 629 Lenters, J.D., Cook, K.H. (1999). Summertime precipitation variability over South America: Role of the
630 large-scale circulation. *Mon. Weather Rev.*, 127, 409–431.
- 631 Li, J. (2014). Terminal fluvial systems in a semi-arid endorheic basin, Salar de Uyuni (Bolivia). Uitgeverij
632 BOX Press, 's-Hertogenbosch, The Netherlands.
- 633 Li, J., Bristow, C.S. (2015). Crevasse splay morphodynamics in a dryland river terminus: Río Colorado in
634 Salar de Uyuni Bolivia. *Quat. Int.*, 377, 71–82. <https://doi.org/10.1016/j.quaint.2014.11.066>
- 635 Li, J., Donselaar, M.E., Hosseini Aria, S.E., Koenders, R., Oyen, A.M. (2014a). Landsat imagery-based

- 636 visualization of the geomorphological development at the terminus of a dryland river system. *Quat.*
637 *Int.*, 352, 100–110. <https://doi.org/10.1016/j.quaint.2014.06.041>
- 638 Li, J., Menenti, M., Mousivand, A., Luthi, S.M. (2014b). Non-vegetated playa morphodynamics using
639 multi-temporal landsat imagery in a semi-arid endorheic basin: Salar de Uyuni, Bolivia. *Remote Sens.*,
640 6, 10131–10151. <https://doi.org/10.3390/rs61010131>
- 641 Li, J., Bristow, C.S., Luthi, S.M., Donselaar, M.E. (2015a). Dryland anabranching river morphodynamics:
642 Río Capilla, Salar de Uyuni, Bolivia. *Geomorphology*, 250, 282–297.
643 <https://doi.org/10.1016/j.geomorph.2015.09.011>
- 644 Li, J., Luthi, S.M., Donselaar, M.E., Weltje, G.J., Prins, M.A., Bloemsma, M.R. (2015b). An ephemeral
645 meandering river system: Sediment dispersal processes in the Río Colorado, Southern Altiplano
646 Plateau, Bolivia. *Zeitschrift für Geomorphol.*, 59, 301–317. <https://doi.org/10.1127/zfg/2014/0155>
- 647 Li, J., Yang, X., Maffei, C., Tooth, S., Yao, G. (2018). Applying independent component analysis on
648 Sentinel-2 imagery to characterize geomorphological responses to an extreme flood event near the
649 non-vegetated Río Colorado Terminus, Salar de Uyuni, Bolivia. *Remote Sens.*, 10, 725.
- 650 Li, J., Tooth, S., Yao, G. (2019). Cascades of sub-decadal, channel-floodplain changes in low-gradient,
651 non-vegetated reaches near a dryland river terminus: Salar de Uyuni, Bolivia. *Earth Surf. Process.*
652 *Landforms*, 44, 490–506. <https://doi.org/10.1002/esp.4512>
- 653 Li, J., Grenfell, M.C., Wei, H., Tooth, S., Ngiem, S. (2020). Chute cutoff-driven abandonment and
654 sedimentation of meander bends along a fine-grained, non-vegetated, ephemeral river on the
655 Bolivian Altiplano. *Geomorphology*, 350, 106917. <https://doi.org/10.1016/j.geomorph.2019.106917>
- 656 Li, J., Zhao, Y., Bates, P., Neal, J., Tooth, S., Hawker, L., Maffei, C., Duan, S. (2021), Digital Elevation
657 Models for topographic characterisation and flood flow modelling along low-gradient, terminal dryland
658 rivers: a comparison of spaceborne datasets for the Río Colorado, Bolivia, *Journal of Hydrology*, in

press.

- Lisenby, P.E., Tooth, S., Ralph, T.J. (2019). Product vs. process? The role of geomorphology in wetland characterization. *Sci. Total Environ.*, 663, 980–991. <https://doi.org/10.1016/j.scitotenv.2019.01.399>
- Malan, H.L., Appleton, C.C., Day, J.A., Dini, J. (2009). Wetlands and invertebrate disease hosts: are we asking for trouble? *Water SA*, 35, 753-767.
- Marshall, L.G., Swisher III, C.C., Lavenue, A., Hoffstetter, R., Curtis, G.H. (1992). Geochronology of the mammal-bearing late Cenozoic on the northern Altiplano, Bolivia. *J. South Am. Earth Sci.*, 5, 1–19.
- McCarthy, T.S., Tooth, S., Kotze, D.C., Collins, N., Wandrag, G., Pike, T. (2010). The role of geomorphology in evaluating remediation options for floodplain wetlands: the case of Ramsar-listed Seekoeivlei, eastern South Africa. *Wetlands Ecology and Management*, 18, 119-134.
- Milan, D., Heritage, G., Tooth, S., Entwistle, N. (2018). Morphodynamics of bedrock-influenced dryland rivers during extreme floods: Insights from the Kruger National Park, South Africa. *GSA Bull.*, 1–17. <https://doi.org/10.1130/B31839.1>
- Millennium Ecosystem Assessment (2005). *Ecosystems and Human Well-Being: Wetlands and Water. Synthesis*. World Resour. Institute, Washington, DC. <https://doi.org/10.1080/17518253.2011.584217>
- Milzow, C., Kgotlhang, L., Kinzelbach, W., Meier, P., Bauer-Gottwein, P. (2009). The role of remote sensing in hydrological modelling of the Okavango Delta, Botswana. *J. Environ. Manage.*, 90, 2252–2260. <https://doi.org/10.1016/j.jenvman.2007.06.032>
- Nicholas, A.P., Walling, D.E. (1997). Modelling flood hydraulics and overbank deposition on river floodplain. *Earth Surf. Process. Landforms*, 22, 59–77.
- Otsu, N. (1979). A threshold selection method from gray-level histograms. *IEEE Trans. Syst. Man. Cybern.*, 9, 62–66. <https://doi.org/10.1109/TSMC.1979.4310076>
- Parker, D. (2000). *Floods (2 Volumes)*. Routledge, London.

- 682 Pekel, J.F., Cottam, A., Gorelick, N., Belward, A.S. (2016). High-resolution mapping of global surface
683 water and its long-term changes. *Nature*, 540, 418–422. <https://doi.org/10.1038/nature20584>
- 684 Piégay, H., Arnaud, F., Belletti, B., Bertrand, M., Bizzi, S., Carbonneau, P., Dufour, S., Liebault, F.,
685 Ruiz-Villanueva, V., Slater, L. (2020). Remotely sensed rivers in the Anthropocene: state of the art
686 and prospects. *Earth Surface Processes and Landforms*, 45, 157-188.
- 687 Ralph, T.J., Hesse, P.P. (2010). Downstream hydrogeomorphic changes along the Macquarie River,
688 southeastern Australia, leading to channel breakdown and floodplain wetlands. *Geomorphology*, 118,
689 48–64. <https://doi.org/10.1016/j.geomorph.2009.12.007>
- 690 Reid I., Frostick L.E. (2011). Channel form, flows and sediments in deserts. In: Thomas, D.S.G. (ed.),
691 *Arid Zone Geomorphology: Process, Form and Change in Drylands*. John Wiley & Sons, Ltd.,
692 Chichester, pp. 301–332.
- 693 Rigsby, C.A., Bradbury, J.P., Baker, P.A., Rollins, S.M., Warren, M.R. (2005). Late Quaternary
694 palaeolakes, rivers, and wetlands on the Bolivian Altiplano and their palaeoclimatic implications. *J.*
695 *Quat. Sci.*, 20, 671–691. <https://doi.org/10.1002/jqs.986>
- 696 Rowberry, M.D., McCarthy, T.S., Thompson, M., Nomnganga, A., Moyo, L. (2011). The spatial and
697 temporal characterisation of flooding within the floodplain wetland of the Nyl River, Limpopo Province,
698 South Africa. *Water SA*, 37, 445-451.
- 699 Schanze, J., Zeman, E., Marsalek, J. (2006). *Flood Risk Management: Hazards, Vulnerability and*
700 *Mitigation Measures*. NATO Science Series, IV Earth and Environmental Sciences, 67. Springer, The
701 Netherlands.
- 702 Schick, A.P. (1988). Hydrologic aspects of floods in extreme arid environments. In: Baker, R., Kochel,
703 R.C., Patton, P.C. (eds.), *Flood Geomorphology*. Wiley, New York, pp. 189–203.
- 704 Slingerland, R., Smith, N.D. (2004). River avulsion and their deposits. *Annu. Rev. Earth Planet. Sci.*, 32,

257–285.

Smith, M.W., Macklin M.G., Thomas, C.J. (2013). Hydrological and geomorphological controls of malaria transmission. *Earth-Science Reviews*, 116, 109–127.

Stromsoe, N., Callow, J.N. (2012). The role of vegetation in mitigating the effects of landscape clearing upon dryland stream response trajectory and restoration potential. *Earth Surf. Process. Landforms*, 37, 180–192. <https://doi.org/10.1002/esp.2240>

Terry, J.P., Garimella, S., Kostaschuk, R.A. (2002). Rates of floodplain accretion in a tropical island river system impacted by cyclones and large floods. *Geomorphology*, 42, 171–182. [https://doi.org/10.1016/S0169-555X\(01\)00084-8](https://doi.org/10.1016/S0169-555X(01)00084-8)

Thito, K., Wolski, P., Murray-Hudson, M. (2016). Mapping inundation extent, frequency and duration in the Okavango Delta from 2001 to 2012. *African J. Aquat. Sci.*, 41, 267–277. <https://doi.org/10.2989/16085914.2016.1173009>

Ticehurst, C., Guerschman, J.P., Chen, Y. (2014). The strengths and limitations in using the daily MODIS open water likelihood algorithm for identifying flood events. *Remote Sens.*, 6, 11791–11809. <https://doi.org/10.3390/rs61211791>

Tomsett C, Leyland J. (2019). Remote sensing of river corridors: a review of current trends and future directions. *River Research and Applications*, 35, 779–803.

Tooth, S. (1999). Floodouts in central Australia, in: Miller, A.J. and Gupta, A. (ed.), *Varieties of Fluvial Form*. John Wiley and Sons, Chichester, pp. 219–247.

Tooth, S. (2000). Downstream changes in dryland river channels: the Northern Plains of arid central Australia. *Geomorphology*, 34, 33–54. [https://doi.org/10.1016/S0169-555X\(99\)00130-0](https://doi.org/10.1016/S0169-555X(99)00130-0)

Tooth, S. (2005). Splay formation along the lower reaches of ephemeral rivers on the Northern Plains of arid central Australia. *J. Sediment. Res.*, 75, 636–649. <https://doi.org/10.2110/jsr.2005.052>

- 728 Tooth, S. (2013). Dryland fluvial environments: assessing distinctiveness and diversity from a global
729 perspective. In: Shroder, J. (Editor in Chief) and Wohl, E.E. (ed.), *Treatise on Geomorphology*.
730 Academic Press, San Diego, CA, Vol. 9, *Fluvial Geomorphology*, pp. 612-644 (DOI:
731 10.1016/B978-0-12-374739-6.00257-8).
- 732 Tooth, S. (2018). The geomorphology of wetlands in drylands: Resilience, nonresilience, or ...?
733 *Geomorphology*, 305, 33–48. <https://doi.org/10.1016/j.geomorph.2017.10.017>
- 734 Tooth, S., McCarthy, T.S., Brandt, D., Hancox, P.J., Morris, R. (2002). Geological controls on the
735 formation of alluvial meanders and floodplain wetlands: The example of the Klip River, eastern Free
736 State, South Africa. *Earth Surf. Process. Landforms*, 27, 797–815. <https://doi.org/10.1002/esp.353>
- 737 Tooth, S., McCarthy, T., Rodnight, H., Keen-Zebert, A., Rowberry, M., Brandt, D. (2014). Late Holocene
738 development of a major fluvial discontinuity in floodplain wetlands of the Blood River, eastern South
739 Africa. *Geomorphology*, 205, 128–141.
- 740 Tooth, S., Rodnight, H., Duller, G.A.T., McCarthy, T.S., Marren, P.M., Brandt, D. (2007). Chronology and
741 controls of avulsion along a mixed bedrock-alluvial river. *Bull. Geol. Soc. Am.*, 119, 452–461.
742 <https://doi.org/10.1130/B26032.1>
- 743 Tooth, S., Rodnight, H., McCarthy, T.S., Duller, G.A.T., Grundling, A.T. (2009). Late Quaternary dynamics
744 of a South African floodplain wetland and the implications for assessing recent human impacts.
745 *Geomorphology*, 106, 278–291. <https://doi.org/10.1016/j.geomorph.2008.11.009>
- 746 Uddin, K., Matin, M. A., Meyer, F. J. (2019). Operational flood mapping using multi-temporal Sentinel-1
747 SAR images: A case study from Bangladesh. *Remote Sensing*, 11(13), 1581.
748 <https://doi.org/10.3390/rs11131581>
- 749 van Toorenenburg, K.A., Donselaar, M.E., Weltje, G.J. (2018). The life cycle of crevasse splays as a key
750 mechanism in the aggradation of alluvial ridges and river avulsion. *Earth Surf. Process. Landforms*,

- 751 43, 2409–2420. <https://doi.org/10.1002/esp.4404>
- 752 Wohl, E., Barros, A., Brunzell, N., Chappell, N.A., Coe, M., Giambelluca, T., Goldsmith, S., Harmon, R.,
753 Hendrickx, J.M.H., Juvik, J., McDonnell, J., Ogden, F. (2012). The hydrology of the humid tropics. *Nat.*
754 *Clim. Chang.*, 2, 655–662. <https://doi.org/10.1038/nclimate1556>
- 755 Woodward, J.C., Tooth, S., Brewer, P.A., Macklin, M.G. (2010). The 4th International Palaeoflood
756 Workshop and trends in palaeoflood science. *Glob. Planet. Chang.*, 70, 1–4.
757 <https://doi.org/10.1016/j.gloplacha.2009.11.002>
- 758 Xu, H. (2006). Modification of normalised difference water index (NDWI) to enhance open water features
759 in remotely sensed imagery. *Int. J. Remote Sens.*, 27, 3025–3033.
- 760 Yang, X., Chen, L. (2017). Evaluation of automated urban surface water extraction from Sentinel-2A
761 imagery using different water indices. *Journal of Applied Remote Sensing*, 11(2), 026016.
762 <https://doi.org/10.1117/1.JRS.11.026016>
- 763 Yang, X., Zhao, S., Qin, X., Zhao, N., Liang, L. (2017). Mapping of urban surface water bodies from
764 sentinel-2 MSI imagery at 10 m resolution via NDWI-based image sharpening. *Remote Sensing*, 9(6),
765 1–19.
- 766 Yang, X., Qin, Q., Grussenmeyer, P., Koehl, M. (2018). Urban surface water body detection with
767 suppressed built-up noise based on water indices from Sentinel-2 MSI imagery. *Remote Sensing of*
768 *Environment*, 219(September), 259–270. <https://doi.org/10.1016/j.rse.2018.09.016>
- 769 Yang, X., Chen, Y., Wang, J. (2020a). Combined use of Sentinel-2 and Landsat 8 to monitor water
770 surface area dynamics using Google Earth Engine. *Remote Sensing Letters*, 11(7), 687–696.
771 <https://doi.org/10.1080/2150704X.2020.1757780>
- 772 Yang, X., Qin, Q., Yésou, H., Ledauphin, T., Koehl, M., Grussenmeyer, P., Zhu, Z., (2020b). Monthly
773 estimation of the surface water extent in France at a 10-m resolution using Sentinel-2 data. *Remote*

774 Sensing of Environment, 244(March), 111803.

775

776 **List of figures**

777

778 Fig. 1 The Altiplano and the Río Colorado: (a) location of the Altiplano in South America; (b) map of the
779 Altiplano, highlighting the study reach of the Río Colorado (red box) near the southeastern margin of the
780 Salar de Uyuni; (c) details of the study reach, showing three avulsion nodes (blue dots), random points
781 used for accuracy assessment of flood mapping (red symbols), and the areas covered by some
782 subsequent figures (red boxes); (d) image showing the downstream reach of abandoning channel D1
783 and newer channel D2; (e) image highlighting an ongoing avulsion along channel D2; (f) TanDEM-X
784 digital elevation model illustrating the characteristically low gradients in the study area.

785

786 Fig. 2 Ground level photos showing the typical channel-floodplain characteristics in the study area: (a)
787 point bar and adjacent channel bed on meander bend 33 along reach B (see the locality in Fig. 3, flow
788 direction away from the camera); (b) channel bed, cutbank and adjacent floodplain surface in the
789 upstream limb of meander bend 33 along reach B (see the locality in Fig. 3, flow direction towards the
790 camera). In both (a) and (b), note the absence of vegetation and the fine-grained sediments (clay, silt,
791 fine sand).

792

793 Fig. 3 (a) Meander bends analyzed in this study along the trunk channel (reach C-B) and a secondary
794 channel (D1) of the Río Colorado (for location, see Fig. 1c). (b)-(c) Example of channel-floodplain
795 dynamics occurring along a short reach of the trunk channel between November 2004 and November
796 2018 (for location, see Part a).

797

798 Fig. 4 Flood maps for the study reach for the years 2004 through 2016 (nb. no Landsat data is available

799 for the years 2012 and 2013 – see SI Table 1). The red lines indicate the trunk channel (reaches C-B)
800 and the secondary channel D1 (see Fig. 1(c)).

801

802 Fig. 5 (a) Flooded area in the study reach for the years 2004 through 2016 in comparison to maximum
803 precipitation totals (daily, 2-day, and 3-day); (b) Relationship between rate of change in flooded area (i.e.
804 ‘wet land’/‘water bodies’) and in maximum precipitation totals (daily, 2-day and 3-day), with rate of
805 change calculated as the difference between two temporally adjacent values, divided by the length of
806 time between the two observation points; (c) Multivariate ENSO Index (MEI) for the years 2004 through
807 2016; MEI values greater than 0 indicate El Niño years and MEI values lower than 0 indicate La Niña
808 years (data available from <https://www.esrl.noaa.gov/psd/enso/mei/table.html>).

809

810 Fig. 6 Satellite images (a-f) illustrating an avulsion in a downstream part of secondary channel D1
811 between November 2004 and November 2018 (for location, see Fig. 1c–d and for scale, see Part a).
812 Increasingly, flow has been diverted from D1 to another secondary channel (D2), leading to gradual
813 abandonment of D1, breaching of levees, and formation and extension of crevasse splays.

814

815 **List of tables**

816

817 Table 1 Summary of the characteristics of the channels and floodplain that were the main focus of study.

818

819 Table 2 Statistics of classification accuracy for Landsat composite images from 2004 through 2016,

820 based on accuracy assessment using visual interpretation and random points.

Fig.1

Fig.2

Fig.3

Fig.4

Fig.5

Fig.6

Table 1

	Channel number	Mean width (m)	Mean channel depth (m)	Mean sinuosity index	Bankfull discharge (m ³ /s)	Unit stream power (W/m ²)	Typical bed/bank sediment	Vegetation
Channels	C	36	1.3	1.19	99	<10	clay, silt, fine sand	No
	B	23	no data	1.37	46	<10	clay, silt, fine sand	
	D1	21.3	no data	1.41	42	<10	clay, silt	
	D2	21	no data	1.16	41	<10	clay, silt	
Floodplain		2234	-	-	-	-	-	No

Table 2

	Producer's accuracy (%)	User's accuracy (%)	Overall accuracy (%)	Kappa coefficient
Mean	91.68	97.33	93.09	0.84
Maximum	100	100	98	0.96
Minimum	79.31	92.86	86	0.72

Supplementary information

Visualisation of flooding along an unvegetated, ephemeral river using Google Earth Engine: implications for assessment of channel-floodplain dynamics in a time of rapid environmental change

Jianguang Li^{1*, 2}, Stephen Tooth³, Kun Zhang⁴, Yang Zhao¹

1 Key Laboratory of Tectonics and Petroleum Resources of the Ministry of Education, China University of Geosciences, Wuhan, 430074, China

2 Key Laboratory of Theory and Technology of Petroleum Exploration and Development in Hubei Province, Wuhan 430074, China

3 Department of Geography and Earth Sciences, Aberystwyth University, Aberystwyth, SY23 3DB, UK

4 Institute of Geological Survey of Qinghai Province, Xining, 810012, China

Correspondence: Key Laboratory of Tectonics and Petroleum Resources of the Ministry of Education, China University of Geosciences, Wuhan, 430074, China

Tel.: +86 27 67883067 fax: +86 27 67883051

E-mail address: jianguangli@cug.edu.cn, jianguangli@gmail.com (J. Li)

SI Fig. 1 Time series of available Landsat imagery and maximum precipitation datasets derived from daily precipitation: vertical lines indicate the timing of Landsat imagery used in this study; blue triangles are 3-day maximum precipitation; black rectangles are 2-day maximum precipitation; and red dots are yearly daily maximum precipitation.

SI Fig. 2 Flow chart showing the procedure for mapping flood extent and pattern.

SI Fig. 3 Fig. 5 Example of a composite image derived from Landsat imagery for the 2016 (i.e. December 2015 through March 2016) rainy season. The images are presented as false colour images of bands 7 (red), 5 (green) and 1 (blue).

SI Fig. 4 Example of flood mapping along a secondary channel (D1) using a 2016 composite image: a) 2016 composite image; b) MNDWI-derived surface water areas (blue) in 2016.

SI Fig. 5 Threshold demarcating flooded areas from dry land areas, as determined by Otsu's method.

SI Fig. 6 Relationships between erosion/deposition and changes in sinuosity of individual channel bends for the years 2004 and 2018 along: a)-b) the trunk channel (reaches C-B);

and c)-d) a secondary channel D1.

SI Table 1 Number of Landsat scenes with cloud cover of <10% for the time period of interest. No Landsat data is available for the years 2012 and 2013.

Date	Year	Number of Scenes	Scenes			
Landsat 5	2004	3	30 Jan 2004	15 Feb 2004	18 Mar 2004	
	2005	2	05 Mar 2005	21 Mar 2005		
	2006	2	03 Feb 2006	08 Mar 2006		
	2007	4	05 Dec 2006	21 Dec 2006	22 Jan 2007	11 Mar 2007
	2008	2	10 Feb 2008	29 Mar 2008		
	2009	1	16 Mar 2009			
	2010	2	13 Dec 2009	15 Feb 2010		
	2011	1	17 Jan 2011			
Landsat 8	2014	3	24 Dec 2013	09 Jan 2014	26 Feb 2014	
	2015	1	01 Mar 2015			
	2016	4	30 Dec 2015	15 Jan 2016	15 Feb 2016	03 Mar 2016

SI Table 2 Details of the high resolution satellite imagery used in this study

Type	Catalog ID	Acq. date	Avg. off nadir angle	Avg. target azimuth	Sensor	Dataset types
Quick Bird-02 (GoogleEarth)	10100100035DE200	02 Nov 2004	8°	293°	QB02	
Worldview-02	1020010001455700	30 Dec 2007	17°	85°	WV01	
	10300100084D5600	09 Dec 2010	13°	173°	WV02	
Pléiades	DS_PHR1B_201307131443591_SE1 _PX_W067S21_0310_02391	13 Jul 2013	16°	33°	PHR1B	Surface reflectance
	DS_PHR1B_201603011443021_FR1 _PX_W067S21_0310_02408	01 Mar 2016	11°	69°	PHR1B	
	DS_PHR1A_201811151436194_FR1 _PX_W067S21_0207_01728	15 Nov 2018	20°	89°	PHR1A	