Aberystwyth University

Fundamental investigations of natural and laboratory generated SAR dose response curves for quartz OSL in the high dose range

Timar-Gabor, A.; Constantin, D.; Buylaert, J. P.; Jain, M.; Murray, A. S.; Wintle, A. G.

Published in:

Radiation Measurements

DOI:

[10.1016/j.radmeas.2015.01.013](https://doi.org/10.1016/j.radmeas.2015.01.013)

Publication date:

2015

Citation for published version (APA):

Timar-Gabor, A., Constantin, D., Buylaert, J. P., Jain, M., Murray, A. S., & Wintle, A. G. (2015). Fundamental investigations of natural and laboratory generated SAR dose response curves for quartz OSL in the high dose range. *Radiation Measurements*, 81, 150-156. <https://doi.org/10.1016/j.radmeas.2015.01.013>

General rights

Copyright and moral rights for the publications made accessible in the Aberystwyth Research Portal (the Institutional Repository) are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the Aberystwyth Research Portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the Aberystwyth Research Portal

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

tel: +44 1970 62 2400

email: is@aber.ac.uk

*Highlights (for review)

- Double saturation exponential laboratory dose response
- Behaviour is inherent to quartz
- Natural dose response curves enter saturation earlier than laboratory dose response curves
- Initial dose dependent sensitivity changes may lead to poor dose recovery at very high doses

Fundamental investigations of natural and laboratory generated SAR dose response curves for quartz OSL in the high dose range

A. Timar-Gabor^{1,2*}, D. Constantin^{1,2,3}, J.P. Buylaert^{4,5}, M. Jain⁵, A.S. Murray⁴, A.G. Wintle^{6,7}

¹ Faculty of Environmental Sciences and Engineering, Babeş-Bolyai University, Cluj-Napoca, Romania

² Interdisciplinary Research Institute on Bio-Nano-Science, Babeş-Bolyai University, Cluj-Napoca, Romania

³ Faculty of Biology and Geology, Babeş-Bolyai University, Cluj-Napoca, Romania

⁴ Nordic Laboratory for Luminescence Dating, Department of Geoscience, Aarhus University, DTU Risø campus, Roskilde, Denmark

⁵ Center for Nuclear Technologies, Technical University of Denmark, DTU Risø campus, Roskilde, Denmark

⁶ Institute of Geography and Earth Sciences, Aberystwyth University, Aberystwyth, UK

⁷ McDonald Institute for Archaeological Research, University of Cambridge, Cambridge

* Corresponding author: alida.timar@ubbcluj.ro

Abstract

SAR-OSL investigations on quartz from Romanian loess resulted in non concordant fine and coarse-grain ages for equivalent doses higher than ~100 Gy. The laboratory dose response for both grain sizes is well represented by a sum of two saturating exponential functions, fine and coarse grains characterised by D_{01} and D_{02} values of ~140 and ~1400 Gy and ~65 and ~650 Gy respectively. Pulsed OSL experiments confirmed that this behaviour is almost certainly inherent to quartz and not caused by contamination with another mineral. Natural dose-response curves do not follow the same pattern and enter saturation much earlier. Analysis of time resolved spectra indicated similar luminescence lifetimes for both fine and coarse quartz grains, and natural and laboratory generated OSL signals seem to use the same non-dose-dependent recombination pathways. The natural signals of a sample with an expected equivalent dose of 2000-2500 Gy were found to be below the saturation level of the laboratory dose response curve for both grain sizes; this also applied to the luminescence signals measured after >5000 Gy given on top of natural doses.

Keywords: quartz; CW-OSL; TR-OSL; SAR protocol; dose response.

1. Introduction

Many thousands of optically stimulated luminescence (OSL) ages have been produced in the last decade using quartz, mainly using the simple single-aliquot regeneration (SAR) protocol (Murray and Wintle, 2000) and the modified SAR protocol (Murray and Wintle, 2003). The basic and fundamental assumption of luminescence dating is that the growth of the luminescence signal in nature can be reproduced under laboratory conditions by performing irradiations with a calibrated beta or gamma source. This comparison is based on the assumption that trapped charge distribution is not dependent on the dose rate, type of radiation or irradiation history before deposition (i.e. before sunlight exposure of the sediment).

In the SAR procedure, a dose response curve is obtained by plotting the ratio of the OSL signal to the response to a test dose. If the OSL signal is derived from a single electron trap and recombination centre, then the form of the dose response curve would be a single saturating exponential (e.g. Bøtter-Jensen et al., 2003). Some such dose response curves have been reported (e.g. Wintle and Murray, 2006); however, many SAR dose response curves for OSL signals from fine grained quartz dominated by the fast component display continuing growth at high doses (e.g. Lowick et al., 2010, 2011; Kreutzer et al., 2012). This behaviour would, in theory, enable higher equivalent doses to be obtained. In practice however, few ages have been obtained by SAR-OSL dating that have been in agreement with independent age control beyond the Eemian. Using multiple grain SAR-OSL procedures, Buylaert et al. (2007) reported natural signals below the laboratory saturation level for a sample with an expected age of ~900 ka. To our knowledge, for quartz that displays a continuing growth at high doses, there are no reports in the literature of natural signals found in saturation.

Our previous studies using fine (4-11 μm) and coarse (63-90 μm) quartz extracted from Romanian loess have shown that natural OSL signals from infinitely old samples are significantly below the laboratory saturation level (Timar-Gabor et al., 2012). Also, it has been reported that ages derived from these two grain size fractions are mutually inconsistent for equivalent doses higher than about 100 Gy, in the case of quartz extracted from both the Lower Danube Basin and the Carpathian Basin (Timar-Gabor et al., 2011, Constantin et al., 2014, Constantin et al. in press, Timar-Gabor et al., in press). Moreover, our previous results derived from quartz extracted from Romanian loess indicate that the laboratory dose response curve does not accurately reflect the growth of the OSL signal in nature (Timar-Gabor and Wintle, 2013). The present work is directed at obtaining more insight into these observations, by performing additional continuous-wave OSL experiments, and by applying time resolved luminescence on quartz extracts; these experiments are designed (i) to test whether the observed luminescence growth is a characteristic of quartz rather than an artefact caused by feldspar contamination, and (ii) to determine whether luminescent recombination occurs at different centres at large doses.

2. Samples, instrumentation and measurement protocol

Experiments presented in the current study have been conducted on archived quartz separates (63-90 μm and 4-11 μm grains) from our previous investigations on Romanian loess. Samples coded as MV have been collected from Mircea Vodă section in Dobrudjea (Timar et al., 2010; Timar-Gabor et al., 2011). MST is the lab code attributed to Mostistea section from the Romanian Plain (Vasiliniuc et al., 2011; Timar-Gabor et al., 2012). CST samples were taken from Costineşti section near the Black Sea shore (Timar-Gabor and Wintle, 2013; Constantin et al., 2014), while samples coded as LCA come from Lunca section in South Western Romania (Constantin et al., in press). More details on these samples are given in the supplementary material (**Table S1**). Continuous-wave optically stimulated luminescence (CW-OSL) measurements on quartz were made in the Cluj Luminescence Dating Laboratory with a Risø TL/OSL DA-20 reader equipped with blue light emitting diodes

(LEDs) emitting at 470 ± 30 nm and IR LEDs emitting at 875 ± 80 nm; luminescence signals were observed through a 7.5 mm thick Hoya U-340 UV filter. Irradiations have been carried out using a ^{90}Sr - ^{90}Y beta source, calibrated using fine and coarse quartz (e.g. Hansen et al., this issue). The dose rate (at the time of measurement) for coarse grains mounted on stainless steel discs was $0.147 \text{ Gy}\cdot\text{s}^{-1}$ and $0.118 \text{ Gy}\cdot\text{s}^{-1}$ for fine grains deposited on aluminium discs. Details of the TL/ OSL reader can be found in Thomsen et al. (2006). The OSL signal was collected in time intervals of 0.154 s. All samples have been analysed using a SAR protocol (Murray and Wintle, 2000, 2003). The OSL signal used for analysis was that obtained for the first 0.308 s of the decay curve minus a background derived from the signal measured between 2.464 and 3.080 s, as had been used in previous studies on Romanian loess (Timar et al., 2010; Timar-Gabor et al., 2011; Timar-Gabor et al., 2012; Timar-Gabor and Wintle, 2013) following the recommendations of Cunningham and Wallinga (2010). All OSL signals analysed were characterised by a rapid decay and the shape of the decay curve is not dose dependent (**Figure S1**). Our previous studies showed that the shape of the linearly modulated OSL signal is not dependent on the age of the sample (Timar-Gabor et al., 2011- figure 4), nor on either the administered dose (Timar-Gabor et al., 2012- figure S1 and S4) or the thermal treatment previously applied (Timar-Gabor et al., 2011- figure 5). This provides evidence that the behaviour reported is characteristic of quartz OSL signals dominated by the fast component, as also reported by other studies (Lowick et al., 2010). Natural (L_n) and regenerated (L_x) signals were measured after a preheat of 10 s at 220°C ; the corresponding responses (T_n and T_x) to a test dose (16 Gy) were measured after a cutheat to 180°C unless otherwise stated. The value of the test dose was kept constant through all measurements for both grain sizes of quartz. A high-temperature bleach was performed after each SAR cycle by stimulating with the blue diodes for 40 s at 280°C (Murray and Wintle, 2003).

Time resolved optically stimulated luminescence (TR-OSL) experiments were carried out at DTU Nutech on a Risø TL/OSL-20 (designated as Reader V) equipped with an integrated pulsing option to control the LEDs, and a Photon Timer attachment to record the TR-OSL (Lapp et al., 2009). All TR-OSL experiments have been carried out using the same measurement parameters as used in the CW-OSL measurements. For stimulating and recording the TR-OSL signals, the total measurement time was set to 100 s, with a pulse period of 500 μs consisting of an “on time” of 50 μs and an “off time” of 450 μs ; this is equivalent to a net stimulation period of 10 s in CW-OSL. A total of 500 data points was used for data collection in pulsed stimulation; the sample was not illuminated during the first and the last five channels. Measurement of dose response curves using pulsed OSL measurements was designed to reproduce the CW-OSL measurement conditions as closely as possible, and to minimise any possible feldspar contamination of the quartz, by: (i) selection of an on time of 50 μs (ii) gating the photomultiplier for counting only during the off period; (iii) ignoring the first 4 μs during the off time in TR-OSL OSL data analysis (Ankjærgaard et al., 2010).

3. Laboratory dose response of quartz OSL

3.1. CW-OSL investigations

1 Previous studies on Romanian loess showed quartz saturation at large doses, especially in the case of fine grains.
2
3 Here we compare the laboratory dose response of fine and coarse grains up to 5kGy. For fine grains, 15 aliquots
4
5 (from different sections in Romania) are shown (**Figure 1a**) one aliquot of MV10 and CAC 2.1.; two aliquots of
6
7 CST_{inf}, MST 2, MST 6, MST 13, MST 19 and three aliquots of LCA15; it can be seen that the saturation
8
9 characteristics are similar and all datasets can be well represented by a sum of two saturating exponential
10 functions:

$$11 \quad I(D) = I_0 + A(1 - \exp(-D/D_{01})) + B(1 - \exp(-D/D_{02}))$$

12
13
14 Any scatter in the data may be due to different origins of the loess as samples come from both SE and SW
15
16 Romania. For coarse grains, 11 aliquots are shown (**Figure 1b**), one aliquot from samples CAC. 2.1, CST_{inf},
17
18 LCA 15 and two aliquots of samples MV8, MST3, MST 17, and MST 19. The scatter is greater than for the 16
19
20 samples taken down the section at Costineşti (Timar-Gabor and Wintle, 2013). This may be due to the higher
21
22 dose range investigated (5000 Gy in the present study compared to 1000 Gy in the previous work) but may also
23
24 suggest a continuity of source material at one site; in that case, **Figs. 1a** and **1b** may show a variation in source
25
26 material across southern Romania. Nevertheless, and despite the observed scatter, the saturation characteristics
27
28 of all samples from a specific grain size are rather similar, but the average behaviour of the two grain sizes is
29 markedly different.

30
31 The reproducibility of the dose response curve was also examined (**Figure S2**). For coarse grains from sample
32
33 MV8, the dose response curve was taken up to 15 kGy. After constructing this first dose response, the sample
34
35 was bleached, given a dose of 170 Gy and then the process repeated; the 2nd dose response agreed with the first.
36
37 As expected, the sensitivity (T_x/T_{nat}) fluctuates, although the response to the constant test dose does not change
38 by more than about 30% from the initial value.

39
40 Saturation characteristics of the dose response curves are not influenced by the thermal treatment used for either
41
42 fine or coarse grains (**Figure S3**). The D_0 values for different thermal treatments are given in **Table S2**. The
43
44 scatter in D_0 is probably affected by the restricted number of points used to construct the dose response and the
45
46 maximum dose given; the latter is not high enough for the dose response to be fully saturated. Nevertheless, it is
47
48 clear that the saturation characteristics of the fine and coarse grains remain significantly different when
49
50 compared to each other no matter what thermal treatment is used. Contrary to the findings of Lai et al. (2008),
51
52 heating the samples to 400°C produced only a trivial change in the shape of the laboratory dose response curve
53 (**Figure S4**).

54
55 If fine grains are derived from the comminution of coarser grains, it is very likely that fine grains have
56
57 experienced many more cycles of bleaching and irradiation than coarse grains. This process is known to sensitise
58
59 coarse grains (Moska and Murray, 2006) and may change the shape of the dose response curve. To test this, nine
60
61 aliquots of coarse grains from different samples were given multiple cycles of bleaching (100 s blue diodes at
62
63 room temperature/ pause 10000s/100 s blue diodes at room temperature) and irradiation (beta dose). All aliquots
64
65

1 sensitized by 60% after 8 cycles of bleaching and irradiation (total dose of approximately 1000 Gy). However,
2
3 there was no noticeable change in the dose response curve shape constructed using the aliquots that were
4
5 subjected to this treatment compared to aliquots from the same sample on which the dose response curve had
6
7 been constructed following the measurement of the natural, at least up to doses of 1000 Gy (**Figure S5**).

8 A fundamental difference that exists in nature between coarse and the fine grains is the past irradiation history,
9
10 fine grains experience a significant alpha dose rate, in contrast to coarse grains. However, after repeated cycles
11
12 of alpha irradiation with doses up 120 kGy (4.8 kGy effective alpha dose, assuming an “a value” of 0.04) prior to
13
14 beta dose response construction, we were unable to detect any significant effect on the saturation characteristics
15
16 of previously-etched quartz grains; thus, it is unlikely that alpha irradiation is causing surface defects that might
17
18 have been responsible for the higher saturation characteristics of fine grains (Constantin et al., this issue).

21 3.2. TR-OSL investigations

22
23 In a previous study (Timar-Gabor et al., in press QI), time-resolved OSL (TR-OSL) measurements were made
24
25 on fine and coarse grains from one sample of Serbian loess from Orlovat. The shape of the TR-OSL was typical
26
27 of quartz (Chithambo, 2003; Denby et al., 2006; Thomsen et al., 2008). In addition, the similarity of the shapes
28
29 with and without prior exposure to IR further confirmed that the OSL was derived from quartz and that no part
30
31 of the signal was from feldspar. Dose response curves for both grain sizes were obtained using the TR-OSL
32
33 signal and were found to be very similar to those using the initial part of the CW-OSL signal. The equivalent
34
35 doses were also in agreement (TR-OSL 171 ± 9 and 170 ± 16 Gy for fine and coarse grains, respectively; the
36
37 equivalent values for CW-OSL were 175 ± 4 and 181 ± 10 Gy). This study was repeated on fine and coarse grains
38
39 from four samples of loess of different ages from Costinești and Lunca sections. The samples were preheated to
40
41 220 °C and stimulated at 125 °C. The IR treatments consisted of stimulation for 200 s at 125°C. TR-OSL curves
42
43 for fine and coarse grains given different doses, recorded both during “on and off times” are presented in
44
45 **Figures 2a and 2b**, respectively. During the “off time”, the signals display a slow decay that can be fitted with
46
47 a single exponential function.

48
49 The aliquots have been measured using a typical SAR protocol measurement sequence, with a test dose of 19
50
51 Gy, and the counts from the photomultiplier were gated to record only during the off period. Data were
52
53 registered in 500 channels of 0.2 seconds, each channel consisting of 400 pulses of stimulation. Data collected
54
55 from 1-4 seconds of signal registration were selected for integration, corresponding to a stimulation time
56
57 interval of 0.32 seconds, a value very similar to that used in CW-OSL (0.308s). The dose response curves for
58
59 TR-OSL (**Figure 2c**) follow the same pattern as those for CW-OSL, showing beyond reasonable doubt that the
60
61 difference observed between coarse and fine grains is inherent in quartz OSL, and not due to some contaminant.
62
63 The lifetimes were calculated for both natural and regenerated TR-OSL signals, as well as for signals obtained
64
65 after IR exposure and for the recycling point in the dose response curve, and these are shown as a function of
66
67 dose in **Figure 2d**. As in the previous study on ORL4 (Timar-Gabor et al., in press QI), the lifetimes for a

stimulation temperature of 125 °C are the same for both grain sizes and agree with the values of 36.5-38.5µs obtained by others (e.g. Chithambo, 2003; Ankjærgaard et al., 2010-figure 1) but there is no marked dependence of lifetime as function of given dose (c.f. Chithambo et al., 2008). These results indicate that the same recombination pathways are used to produce OSL in both fine and coarse grained quartz and these pathways are independent of dose. They also suggest that the second saturation exponential term observed in the dose response curve is not an effect of the existence of multiple recombination centres emitting within our detection window.

4. Natural dose response

Following the approach of Chapot et al. (2012), we have calculated the average sensitivity-corrected natural signals down the section at Costineşti and plotted them as a function of the expected equivalent dose. The latter were calculated using the measured dose rate and the expected ages derived from a model based on changes in magnetic susceptibility down section (Constantin et al., 2014). A relative error of 10% was assigned to the paleomagnetic ages. Fine and coarse grains from 25 samples of loess from Costineşti with expected doses up to 500 Gy were used (Timar-Gabor and Wintle, 2013). These results are shown in **Figures 3a and 3b**, together with the value for “an infinitely old sample” (Timar-Gabor et al., 2012), with expected doses of between 2000 and 2500 Gy, depending on grain size. The natural dose response of the infinitely old sample is about 60% of the laboratory saturation level for fine grains and 80% of the laboratory saturation level in the case of coarse grains. These results provide further evidence that natural signals from infinitely old samples from this region do not fall on the laboratory dose response curves. By comparing **Figures 3a and 3b**, it is seen that the differences between the natural and laboratory dose response curves are more pronounced in the case of fine grains. Based on the dose response curves presented, the natural response seems to overestimate the laboratory response in the 100-400 Gy region, while for higher doses, as in the case of fine grains, the natural signals show earlier saturation.

5. Other dose response curves

5.1. Multiple-aliquot additive-dose with 110 °C TL correction

A new multiple-aliquot additive-dose (MAAD) procedure was applied, in which the OSL responses of all aliquots were normalised using the 110 °C TL peak measured in response to a test dose given before any other laboratory treatment, such as irradiation or preheating. Murray and Wintle (2000) pointed out that a subsequent test dose (as used in the standard for of SAR) did not monitor sensitivity change occurring during measurement of the natural OSL signal; they further showed that a prior 110°C TL measurement could be used for this purpose, if the changes in the sensitivity of the two signals were directly proportional, and Singhvi et al. (2011) later tested this suggestion. In our MAAD procedure, we used 96 aliquots of fine grains from CST 3, which had an equivalent dose of 105 ± 3 Gy as derived using the standard SAR protocol. Immediately following delivery

of a 4 Gy test dose, the 110 °C TL peak was measured by heating to 180 °C. Subsequently the aliquots were divided into 12 groups of 8 aliquots and irradiated with doses ranging from 10 to 2580 Gy. Following a preheat for 10 s at 220 °C, the OSL was measured at 125 °C for 40 s, and this signal was normalised using the previously measured 110 °C TL response.

The MAAD dose response curve is given in **Figure 4** and the equivalent dose (103 ± 20 Gy) obtained by extrapolation of a single saturating exponential function (which was found to be the best fit for the presented dataset) is indistinguishable from the SAR result (105 ± 3 Gy). The scatter observed for each dose point is intriguing, possibly suggesting that individual aliquots have either a range of TL responses to the initial 4 Gy dose or different OSL responses to added dose. Either explanation is surprising, because fine grains are expected to have a homogenous response because of the large number of grains on each disc. Due to this high degree of scatter, a quantitative assessment based on fitting parameters of saturation characteristics cannot be performed with confidence. However, it is important to note that the MAAD dose response is not fully saturated for doses over 2000 Gy and thus grows to higher doses than the natural dose response, which is fully saturated at doses about 500-1000 Gy (**Figure 3**).

5.2. The effect of adding a large dose on top of natural signals

In an earlier study, Timar-Gabor and Wintle (2013) added 1816 Gy on top of the natural dose for fine grains from sample CST 6 ($D_e = 197 \pm 7$ Gy) and 1676 Gy for coarse grains from another sample, CST 1 ($D_e = 116 \pm 8$ Gy). The light levels obtained were compared with those reached by the laboratory dose response curve constructed using the SAR procedure using doses up to 2300 Gy. For the coarse grains, the signal seemed to be in saturation, while for fine grains the signal appeared to be below the maximum value obtained in the laboratory. However, the dose response curves did not show complete saturation. In our study, we have given additional doses of 8000 Gy to the fine grains and 5000 Gy to the coarse grains for the same sample, MST 7. Laboratory dose response curves were then constructed using doses up to 10000 Gy. For both grain sizes, signals from aliquots given added doses are below the saturation levels of the laboratory dose responses; this difference is greatest for fine grains (**Figure 5**). It seems likely that quartz cannot be used to accurately measure a known given dose at high doses (see **Figure S6** and **Table S3** -fine grains and **Figure S7** and **Table S4** -coarse grains for further information), and that signal instability is not likely to be the cause of underestimation of the natural signal relative to the saturation level in the infinitely old sample. In contrast, these results strongly suggest that, at large doses, sensitivity changes in the first measurement cycle are not adequately corrected for using the response to a test dose given either before or after measurement of the signal of interest. They also demonstrate the need to construct laboratory dose response curves up to full saturation before pertinent conclusions regarding the saturation parameters can be drawn.

6. Summary and Conclusions

1 SAR measurement sequences carried out on fine (4-11 μm) and coarse (63-90 μm) grained quartz extracts from
 2
 3 loess deposits at four sites in the south of Romania have confirmed previously published work that shows the
 4
 5 SAR laboratory dose response curves obtained for the two grain sizes to be quite different. For both grain sizes,
 6
 7 the sum of two exponential functions is required to fit the data, characterised by D_{01} and D_{02} values of ~ 140 and
 8
 9 ~ 1400 Gy for fine grains and ~ 65 and ~ 650 Gy in the case of coarse grains, respectively, when doses up to 5000
 10 Gy are given (**Figure 1**). Only when the laboratory dose was extended up to 9 kGy is the fine-grain signal seen
 11 to be in full saturation. Laboratory saturation characteristics are not affected by previous irradiation, bleaching,
 12
 13 or the thermal treatments employed.
 14
 15 TR-OSL measurements on fine and coarse grains showed signals typical of quartz (**Figures 2a and b**), with
 16
 17 lifetime values independent of dose (**Figure 2d**). These results imply that the second exponential component in
 18
 19 the dose response curve is not a result of a varying contribution from different luminescent centres.
 20
 21 For doses higher than about 200 Gy natural and laboratory dose response curves for fine grains diverge (**Figure**
 22
 23 **3a**), with natural signals showing earlier saturation. Based on the divergence shown for these samples from
 24
 25 Costinești, it is tempting to suggest that an upper limit of $2 D_{01}$ could be applied to values of D_e determined
 26
 27 using SAR, as suggested by Wintle and Murray (2006) for single exponential growth. For these samples, Timar-
 28
 29 Gabor and Wintle (2013, Figure 2c) obtained a value of $D_{01} = 76$ Gy when they fitted a double exponential to
 30
 31 the average dose response curve for all samples from this section constructed using doses up to 1200 Gy.
 32
 33 However, as shown in **Figure 1a**, D_{01} ranges between 131 ± 20 and 200 ± 24 Gy when doses up to 5000 Gy
 34
 35 were used to construct the dose response curve; for CST_{inf} , the value was 144 ± 19 Gy. It is thus not possible to
 36
 37 provide firm numerical guidance on the maximum value of D_e that can be determined reliably. In addition, the
 38
 39 comparison is constrained by the uncertainty in the D_e predicted down section based on the dose rate and age
 40
 41 from the palaeomagnetic model, though likely error bars are given in **Figure 1a**. For 63-90 μm quartz, it is
 42
 43 difficult to assess the degree of overlap of the natural and laboratory dose response due to the scatter of the
 44
 45 datapoints (**Figure 3b**).
 46
 47 The multiple-aliquot additive dose response curve (**Figure 4**) seems to grow to higher doses than the natural
 48
 49 dose response; while there is agreement between the values obtained by SAR and MAAD for equivalent doses
 50
 51 ~ 100 Gy, the signals measured after adding a dose of the magnitude of the SAR saturation level (5000 Gy for
 52
 53 coarse grains; 8000 Gy for fine grains) on top of the natural dose were found to be significantly below the
 54
 55 saturation level (**Figure 5**). This suggests an initial dose-dependent sensitivity change that is not corrected for
 56
 57 by the use of the response to a test dose, whether given before or after the signal of interest.
 58
 59 In conclusion, several lines of investigation, such as signal contamination and the effects of prior dose and
 60
 61 thermal treatments, were unable to identify the cause of either the differences between quartz fine-grained and
 62
 63 coarse-grained dose response curves, or the age under-estimation at high doses. Although our previous studies
 64
 65 have shown that acceptable recovered-to-given dose ratios could be obtained up to ~ 500 Gy (Timar-Gabor et
 al., 2011, Timar-Gabor et al., 2012, supplementary material) or even ~ 1500 Gy (Constantin et al., 2014) when

doses are given after a laboratory bleach, our present study suggests that age underestimation may, in part, be caused by poor dose recovery at very high doses. Further investigations in this high dose range are clearly needed and it is recommended that adding a large dose on top of the natural and comparing the measured signal to the laboratory saturation limit should be incorporated as a standard test for evaluating the performance of the SAR protocol, especially when applications are carried out in the high dose range.

Acknowledgements

A.T-G. and D.C. acknowledge the financial support from a grant of the Romanian National Authority for Scientific Research CNCS-UEFISCDI, PN-II-RU-TE-2011-3-0062, nr. 73/05.10.2011.D.C. also acknowledges the financial support of the Sectorial Operational Programme for Human Resources Development 2007-2013, co-financed by the European Social Fund under the project POSDRU/159/1.5/S/133391-“Doctoral and postdoctoral excellence programs for training highly qualified human resources for research in the fields of Life Sciences, Environment and Earth”.

References

1. Ankjærgaard, C., Jain, M., Thomsen K.J., Murray A.S., 2010. Optimising the separation of quartz and feldspar optically stimulated luminescence using pulsed excitation. *Radiation Measurements* 45, 778-785.
2. Buylaert, J.-P., Vandenberghe, D., Murray, A.S., Huot, S., De Corte, F., Van den haute, P., 2007. Luminescence dating of old (>70ka) Chinese loess: a comparison of single-aliquot OSL and IRSL techniques. *Quaternary Geochronology* 2, 9-14.
3. Bøtter-Jensen, L., McKeever, S.W.S., Wintle, A.G., 2003. *Optically Stimulated Luminescence Dosimetry*. Elsevier, 355 p, ISBN 0 444 50684 5.
4. Chapot, M.S., Roberts, H.M., Duller, G.A.T., Lai, Z.P., 2012. A comparison of natural-and laboratory-generated dose response curves for quartz optically stimulated luminescence signals from Chinese Loess. *Radiation Measurements* 47, 1045-1052.
5. Chithambo, M. L., 2003. Dependence of the thermal influence on luminescence lifetimes from quartz on the duration of optical stimulation. *Radiation Measurements* 37, 167-175.
6. Chithambo, M.L., Ogundare, F.O., Feathers, J., Hong, D.G., 2008. The dependence of luminescence lifetimes on additive irradiation on natural sedimentary quartz: sands from Santa Elina, Brazil. *Physica Status Solidi (c)* 2, 630-633.
7. Constantin, D., Begy, R., Vasiliniuc, S., Panaiotu, C., Necula, C., Codrea, V., Timar-Gabor, A., 2014. High-resolution OSL dating of the Costinești section (Dobrega, SE Romania) using fine and coarse quartz. *Quaternary International* 334-335, 20-29.

- 1 8. Constantin, D., Camenita, A., Panaiotu, C., Necula, C., Codrea, V., Timar-Gabor, A., in press. Fine and
2 coarse-quartz SAR-OSL dating of Last Glacial loess in Southern Romania. *Quaternary International*,
3 doi:10.1016/j.quaint.2014.07.052.
4
- 5 9. Constantin, D., Buylaert, J.-P., Jain, M., Murray, A.S., Timar-Gabor, A., submitted. Quartz luminescence
6 response to a mixed alpha - beta field: Investigations on Romanian loess. *Radiation Measurements*.
7
- 8 10. Cunningham, A.C., Wallinga, J., 2010. Selection of integration time intervals for quartz OSL decay curves.
9 *Quaternary Geochronology* 5, 657-666.
10
- 11 11. Denby, P.M., Bøtter-Jensen, L., Murray, A.S., Thomsen K.J., Moska, P., 2006. Application of pulsed OSL
12 to the separation of the luminescence components from a mixed quartz/feldspar sample. *Radiation*
13 *Measurements* 41, 774-779.
14
- 15 12. Hansen, V., Murray, A.S., Buylaert, J-P., Yeo, E-Y., Thomsen, K., submitted. A new irradiated quartz for
16 beta source calibration. *Radiation Measurements*.
17
- 18 13. Kreutzer, S., Fuchs, M., Meszner, S., Faust, D., 2012. OSL chronostratigraphy of a loess-palaeosol sequence
19 in Saxony/Germany using quartz of different grain sizes. *Quaternary Geochronology* 10, 102-109.
20
- 21 14. Lai, Z.P., Brückner, H., Fülling, A., Zöller, L., 2008. Effects of thermal treatment on the growth curve shape
22 for OSL of quartz extracted from Chinese loess. *Radiation Measurements* 43, 763-766.
23
- 24 15. Lapp, T., Jain, M., Ankjærgaard, C., Pirtzel, L., 2009. Development of pulsed stimulation and Photon Timer
25 attachments to the Risø TL/OSL reader. *Radiation Measurements* 44, 571-575.
26
- 27 16. Lowick, S.E., Preusser, F., Wintle, A.G., 2010. Investigating quartz optically stimulated luminescence dose-
28 response curves at high doses. *Radiation Measurements* 45, 975-984.
29
- 30 17. Lowick, S.E., Preusser, F., 2011. Investigating age underestimation in the high dose region of optically
31 stimulated luminescence using fine grain quartz. *Quaternary Geochronology* 6, 33-41.
32
- 33 18. Moska, P., Murray A.S., 2006. Stability of the quartz fast-component in insensitive samples. *Radiation*
34 *Measurements* 41, 878 – 885.
35
- 36 19. Murray, A.S., Wintle, A.G., 2000. Luminescence dating of quartz using an improved single-aliquot
37 regenerative-dose protocol. *Radiation Measurements* 32, 57-73.
38
- 39 20. Murray, A.S., Wintle, A.G., 2003. The single aliquot regenerative dose protocol: potential for improvements
40 in reliability. *Radiation Measurements* 37, 377-381.
41
- 42 21. Singhvi, A.K., Stokes, S.C., Chauhan, N., Nagar, Y.C., Jaiswal, M.J., 2011. Changes in natural OSL
43 sensitivity during single aliquot regeneration procedure and their implications for equivalent dose
44 determination. *Geochronometria* 38, 231-241.
45
- 46 22. Thomsen, K.J., Bøtter-Jensen, L., Denby, P.M., Moska P., Murray, A.S., 2006. Developments in
47 luminescence measurement techniques. *Radiation Measurements* 41, 768–773.
48
- 49 23. Thomsen, K.J., Jain, M., Murray A.S., Denby, P.M., Roy, N., Bøtter-Jensen, L., 2008. Minimising feldspar
50 OSL contamination in quartz UV-OSL using pulsed blue stimulation. *Radiation Measurements* 43, 752-757.
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

24. Timar, A., Vandenberghe, D., Panaiotu, E.C., Panaiotu, C.G., Necula, C., Cosma, C., Van den haute, P., 2010. Optical dating of Romanian loess using fine-grained quartz. *Quaternary Geochronology* 5, 143-148.
25. Timar-Gabor, A., Vandenberghe, D.A., Vasiliniuc, S., Panaiotu, C.E., Panaiotu, C.G., Dimofte, D., Cosma, C., 2011. Optical dating of Romanian loess: a comparison between sand-sized and silt-sized quartz. *Quaternary International* 240, 62-70.
26. Timar-Gabor, A., Vasiliniuc, Ș., Vandenberghe, D.A.G., Cosma, C., Wintle, A.G., 2012. Investigations on the reliability of SAR-OSL equivalent doses obtained for quartz samples displaying dose response curves with more than one component. *Radiation Measurements* 47, 740-745.
27. Timar-Gabor, A., Wintle, A.G., 2013. On natural and laboratory generated dose response curves for quartz of different grain sizes from Romanian loess. *Quaternary Geochronology* 18, 34-40.
28. Timar-Gabor, A., Constantin, D., Marković, S. B., Jain, M., in press. Extending the area of investigation of fine versus coarse quartz optical ages from the Lower Danube to the Carpathian Basin. *Quaternary International*
29. Vasiliniuc, S., Timar-Gabor, A., Vandenberghe, D.A.G., Panaiotu, C.G., Begy, R.Cs., Cosma, C., 2011. A high resolution optical dating study of the Mostiștea loess-palaeosol sequence (SE Romania) using sand-sized quartz. *Geochronometria* 38, 34-41.
30. Wintle, A.G., Murray, A. S., 2006. A review of quartz optically stimulated luminescence characteristics and their relevance in single-aliquot regeneration dating protocols. *Radiation Measurements* 41, 369 – 391.

Figure captions

Figure 1: Laboratory dose response of (a) 15 aliquots of fine grained (4-11 μm) quartz and (b) 11 aliquots of coarse grained (63-90 μm) quartz. For fine grains, the individual values for D_{01} range between 131 ± 20 Gy and 200 ± 24 Gy, while the D_{02} values are between 1252 ± 119 Gy and 1917 ± 280 Gy. In the case of coarse grain, values for D_{01} range between 30 ± 3 Gy and 68 ± 6 Gy while the minimum and maximum values for D_{02} are 317 ± 26 Gy and 705 ± 120 Gy. The average dose response curve for each grain size is represented as a solid line.

Figure 2: TR-OSL signals (photon arrival time distributions-PAT) for one representative aliquot of (a) fine and (b) coarse grains of sample CST 3 recorded after different doses. (c) Dose response curves for fine (4-11 μm) grains and coarse (63-90 μm) grains of sample CST 3 constructed using TR-OSL. (d) Average lifetimes obtained as function of dose. The lifetimes of natural signals are depicted as stars. The IR stimulation was performed in a pseudo-CW stimulation manner (on time 500 μs ; off time 4.5 μs) for 100 s at 125 °C. Each datapoint represents the average value obtained on 10 aliquots.

1 **Figure 3:** The average sensitivity-corrected natural signal for 26 samples from Costinești **(a)** fine and **(b)** coarse
2 grains plotted as function of their expected equivalent dose. The average laboratory dose response curve (based
3 on data taken up to 5000 Gy) is displayed for each grain size.
4
5
6
7

8 **Figure 4:** Multiple aliquot additive dose response curve obtained using 110 °C TL peak for normalisation.
9
10

11 **Figure 5:** Normalised luminescence signals for sample MST 7 ($De = 149 \pm 3$ Gy- fine grains; $De = 191 \pm 17$
12 Gy- coarse grains); following irradiation to a dose of **(a)** 8000 Gy for fine grains and **(b)** 5120 Gy for coarse
13 grains given on top of the natural dose.
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

Figure 1

Figure

Figure 2

Figure 3

Figure 4

Figure

Figure 5

1
2
3
4
SUPPLEMENTARY- Fundamental investigations of natural and laboratory generated SAR dose response curves for quartz OSL in the high dose range

5
6
Table S1: Additional information on investigated samples:

Sample code	De 4-11 μm quartz (Gy)	De 63-90 μm quartz (Gy)	Reference
MV 2	32 ± 1	46 ± 4	Timar-Gabor et al. 2011
MV 8	209 ± 3	247 ± 8	Timar-Gabor et al. 2011
MV 10	310 ± 9	319 ± 15	Timar-Gabor et al. 2011
CAC 2.1.	126 ± 4	119 ± 9	Constantin et al. 2012
MST 2	113 ± 2	130 ± 10	Vasiliniuc et al., 2011; Timar-Gabor et al. 2012
MST 3	151 ± 4	153 ± 4	Vasiliniuc et al., 2011; Timar-Gabor et al. 2012
MST 6	147 ± 2	185 ± 9	Vasiliniuc et al., 2011; Timar-Gabor et al. 2012
MST 7	149 ± 3	191 ± 17	Vasiliniuc et al., 2011; Timar-Gabor et al. 2012
MST 13	195 ± 2	277 ± 15	Vasiliniuc et al., 2011; Timar-Gabor et al. 2012
MST 17	264 ± 9	279 ± 28	Vasiliniuc et al., 2011; Timar-Gabor et al. 2012
MST 19	289 ± 9	288 ± 57	Vasiliniuc et al., 2011; Timar-Gabor et al. 2012
LCA 15	113 ± 2	117 ± 5	Constantin et al. in press
CST 1 $\rightarrow$ CST 25	$90 \pm 1 \rightarrow 409 \pm 12$	$116 \pm 8 \rightarrow 470 \pm 38$	Constantin et al. 2014, Timar-Gabor and Wintle 2013
Cst inf.	650 ± 20	628 ± 47	Timar-Gabor et al. 2012

27
28
29
30
Figure S1: CW-OSL decay curves as a function of dose compared to the calibration quartz (4.81 Gy) OSL decay curve. The data are normalized to the number of counts in the first channel (first 0.15 s of the stimulation time).

SUPPLEMENTARY- Fundamental investigations of natural and laboratory generated SAR dose response curves for quartz OSL in the high dose range

Figure S2: Dose response curve reproducibility test for a coarse quartz aliquot of sample MV8 (see text for experimental details). The first growth is represented by circles while the second growth is represented by stars. Repeat points for the first and second dose responses are represented by up and down triangles respectively. The inset shows the change in sensitivity monitored by the response to the test dose.

Figure S3: Dose response curves constructed up to 2000 Gy using different combinations of preheat/cutheat treatments, for a sample of fine quartz. Fitting parameters in the case of this particular sample, as well as the coarse quartz counterpart material, are given in the table below.

SUPPLEMENTARY- Fundamental investigations of natural and laboratory generated SAR dose response curves for quartz OSL in the high dose range

Table S2: Fitting parameters for OSL dose response curves constructed up to 2000 Gy for different thermal treatments. Please note that fitting parameters should be regarded as an indication of a specific trend rather than a quantitative measure, due to the restricted number of points used and dose range investigated.

Sample	y_0	y_0 error	A_1	A_1 error	D_{01}	D_{01} error	A_2	A_2 error	D_{02}	D_{02} error	Reduced χ^2	R^2
4 – 11 μmMST 2												
Ph 220 cth 180	0.09	0.07	4.8	0.4	105	11	11.7	0.3	826	56	0.007	1.000
Ph 220 cth 180	0.08	0.12	5.0	0.8	112	20	12.2	0.6	836	101	0.020	0.999
Ph 220 cth 220	0.09	0.09	5.3	0.5	108	13	10.2	0.3	1035	131	0.012	1.000
Ph 220 cth 220	0.08	0.11	3.8	0.5	82	14	11.1	0.4	761	68	0.016	0.999
Ph 260 cth 260	0.02	0.13	3.6	0.5	72	15	10.3	0.4	629	59	0.021	0.999
Ph 260 cth 260	0.08	0.07	4.7	0.4	107	12	8.2	0.3	871	94	0.007	1.000
Ph 280 cth 280	0.07	0.08	4.2	0.4	91	11	7.4	0.3	675	64	0.008	1.000
Ph 280 cth 280	0.07	0.07	3.4	0.3	82	10	8.1	0.3	645	45	0.006	1.000
Sample	y_0	y_0 error	A_1	A_1 error	D_{01}	D_{01} error	A_2	A_2 error	D_{02}	D_{02} error	Reduced χ^2	R^2
63-90 μmMST 3												
Ph 220 cth 180	0.09	0.07	3.2	0.3	47	8	3.9	0.3	762	163	0.02	1.00
Ph 220 cth 180	0.08	0.12	2.4	0.6	41	17	4.2	0.5	464	122	0.05	0.99
Ph 220 cth 220	0.09	0.09	1.7	0.3	28	8	5.3	0.3	252	22	0.01	1.00
Ph 220 cth 220	0.08	0.11	3.0	0.4	50	11	3.7	0.3	657	157	0.02	1.00
Ph 260 cth 260	0.02	0.13	2.2	0.2	28	4	2.2	0.2	256	36	0.00	1.00
Ph 260 cth 260	0.08	0.07	2.1	0.3	38	10	5.8	0.3	431	45	0.01	1.00
Ph 280 cth 280	0.07	0.08	1.7	1.0	29	17	2.0	1.0	145	68	0.02	0.99
Ph 280 cth 280	0.07	0.07	2.8	0.4	45	9	1.5	0.3	394	162	0.01	0.99

SUPPLEMENTARY- Fundamental investigations of natural and laboratory generated SAR dose response curves for quartz OSL in the high dose range

Figure S4: Dose response curves for fine and coarse quartz grains constructed before and after heating the sample to 400 °C.

SUPPLEMENTARY- Fundamental investigations of natural and laboratory generated SAR dose response curves for quartz OSL in the high dose range

Figure S5: (a) Variations in OSL sensitivity as a function of bleach/dose cycle obtained using nine coarse quartz aliquots of samples collected from Mircea Voda, Costinesti and Mostistea. The samples were first optically zeroed using a double blue stimulation at room temperature for 100 s with 10 ks pause in between. The aliquots were then given a 170 Gy dose and the OSL signal was measured using a blue stimulation at 125 °C for 40s. This was repeated for five times in order to accumulate a dose of ~ 1000 Gy after bleaching. A dose-response curve was then built using seven regenerative doses up to ~ 1050 Gy. The data represent the net OSL signals obtained in each cycle normalized to the OSL signal from the first cycle. (b) Comparison between the saturation characteristics (D_{01} , D_{02}) obtained for dose-response curves constructed after multiple bleach/dose cycles (open stars) and the values obtained for dose-response curves constructed for D_e measurement, on different aliquots. It can be noted that there is a difference between the individual values (which is to be expected, due to the fact that different aliquots of coarse grains are investigated ; i.e. see scatter in fig 1.b), but remain consistent within error limits.

SUPPLEMENTARY- Fundamental investigations of natural and laboratory generated SAR dose response curves for quartz OSL in the high dose range

Figure S6: Normalised luminescence signal for sample MST 7 4-11 μm quartz, with an equivalent dose of 149 Gy following irradiation with a dose of 2000 Gy.

Table S3: Further results of adding a laboratory dose on top of natural doses for fine quartz grains of samples MST7, MST11 and MST 17.

Sample MST 7 4-11 μm De=149 $\pm$ 3 Gy

Given dose (Gy)	MEASURED DOSE	Nr of aliq	Measured/Given dose
"NATURAL"	149 $\pm$ 3 Gy	6	-
NAT + 99 Gy=248Gy	236 $\pm$ 3 Gy	2	0.95 $\pm$ 0.02
	237 $\pm$ 3 Gy		
NAT + 198 Gy=347Gy	348 $\pm$ 5 Gy	2	0.99 $\pm$ 0.02
	337 $\pm$ 5 Gy		
NAT + 397 Gy=546Gy	491 $\pm$ 8 Gy	2	0.89 $\pm$ 0.02
	485 $\pm$ 10 Gy		
NAT + 595 Gy=744Gy	699 $\pm$ 16 Gy	2	0.95 $\pm$ 0.02
	718 $\pm$ 15 Gy		
NAT + 977 Gy=1126 Gy	1088 $\pm$ 25 Gy	3	0.96 $\pm$ 0.03
	1028 $\pm$ 17 Gy		
	149 $\pm$ 3 Gy		
NAT + 2000 Gy=2149 Gy	1373 $\pm$ 24 Gy	1	0.64 $\pm$ 0.01
NAT + 4508 Gy=4657 Gy	1989 $\pm$ 50 Gy	1	0.43 $\pm$ 0.01
NAT + 7938 Gy=8087 Gy	2930 $\pm$ 83 Gy	1	0.36 $\pm$ 0.01

Sample MST 11 μm De=173 $\pm$ 4 Gy

Given dose (Gy)	MEASURED DOSE	Nr of aliq	Measured/Given dose
"NATURAL"	173 Gy	10	-
NAT + 175 Gy=348 Gy	341 $\pm$ 11 Gy	3	0.98 $\pm$ 0.04

Sample MST 17 μm De=264 $\pm$ 9 Gy

Given dose (Gy)	MEASURED DOSE	Nr of aliq	Measured/Given dose
"NATURAL"	264 $\pm$ 9 Gy	7	-
NAT + 705 Gy=969 Gy	924 $\pm$ 51 Gy	1	0.95 $\pm$ 0.06

SUPPLEMENTARY- Fundamental investigations of natural and laboratory generated SAR dose response curves for quartz OSL in the high dose range

Figure S7: Normalised luminescence signal for sample MST 7 63-90 µm quartz, with an equivalent dose of 170 Gy following irradiation with a dose of 2000 Gy.

Table S4: Further results of adding a laboratory dose on top of natural doses for coarse quartz grains of sample MST7.

Sample MST 7 63-90 µm De=170±8Gy n=9

Given dose (Gy)	MEASURED DOSE	Nr of aliq	Measured/ Given dose
“NATURAL”	170 ± 8 Gy	8	-
NAT + 5000 Gy	1121 Gy	1	0.22
NAT + 2000 Gy	1197 Gy	1	0.55
NAT + 800 Gy	830 Gy	1	0.86
NAT +200 Gy	330 Gy	1	0.89
NAT +104 Gy	258 ± 12 Gy	5	0.94±0.06