

Aberystwyth University

SEVIRI PrePro: A Novel Software Tool for the Pre-processing of SEVIRI Geostationary Orbit EO Data Products

Petropoulos, George; Anagnostopoulos, Vasileios

Published in: Environmental Modelling and Software DOI:

10.1016/j.envsoft.2016.03.015

Publication date: 2016

Citation for published version (APA):

Petropoulos, G., & Anagnostopoulos, V. (2016). SEVIRI PrePro: A Novel Software Tool for the Pre-processing of SEVIRI Geostationary Orbit EO Data Products. *Environmental Modelling and Software*, 82, 321-329. https://doi.org/10.1016/j.envsoft.2016.03.015

General rights

Copyright and moral rights for the publications made accessible in the Aberystwyth Research Portal (the Institutional Repository) are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the Aberystwyth Research Portal for the purpose of private study or You may not further distribute the material or use it for any profit-making activity or commercial gain

- · You may freely distribute the URL identifying the publication in the Aberystwyth Research Portal

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

tel: +44 1970 62 2400 email: is@aber.ac.uk

1 2

3

4 5

6

7

8 9

10 11

12

SEVIRI PrePro: A Novel Software Tool for the Pre-processing of SEVIRI Geostationary Orbit EO Data Products

George Petropoulos^{1*}, Vasileios Anagnostopoulos^{2,3}

¹University of Aberystwyth, Department of Geography and Earth Sciences, SY23 2EJ, Wales, United Kingdom ²Distributed and Knowledge Management Systems Lab, National Technical University of Athens, Greece ³InfoCosmos, Pindou 71, 13341, Athens, Greece

*Author for correspondence: <u>george.petropoulos@aber.ac.uk</u>; Tel: +44-0-1970-621861

ABSTRACT

13 The Spinning Enhanced Visible and Infrared Imager (SEVIRI) is a geostationary orbit multispectral

sensor on-board the MSG Earth Observation (EO) platform, acquiring data over Earth's land surface from the optical to infrared parts of electromagnetic spectrum every 15 minutes. SEVIRI data

16 include also a number of operational products that are all provided to the user's community at no

17 cost via EUMETSAT or LSA SAF portals.

Herein an open access stand-alone software product developed in Java programming language is presented for automating key pre-processing to all the operationally distributed products distributed by the SEVIRI radiometer. The software tool, named Seviri PrePro, makes use of present day multi-core processors, and is being able to process very large datasets in a short time period, making it appropriate as well for use in a High Performance Computing (HPC) environment. The practical usefulness of this tooklit is demonstrated herein as well using as a case study the SEVIRI evapotranspiration (ET) product.

The development and distribution of SEVIRI PrePro is of significant importance to the SEVIRI users' community and is also very timely given that, to our knowledge, no similar software tool is openly available at present. Use of this tool aims at supporting the wider dissemination and implementation of SEVIRI all operational products in general. It is anticipated to make a significant contribution to a large number of practical applications requiring use of SEVIRI data, including, but not limited, weather forecasting and global climate monitoring at a range of geographical scales.

31

32 KEYWORDS: Earth Observation, SEVIRI, pre-processing, geostationary, operational products,
 33 software tool

34

35 **1. INTRODUCTION**

Monitoring the inter-related processes, feedbacks and exchanges between the biosphere, atmosphere and hydrosphere that inherently shape the physical environments within our planet is a topic of key research priority today to be addressed (Mason and Calow, 2012; North et al., 2015). These complex land-surface-atmosphere interactions are important drivers of weather and climate systems and govern the terrestrial hydrological, energy and biogeochemical cycles which are

41 responsible for the existence of life in the planet (Wood et al., 2011; Destouni et al. 2013).

42 In the last decades, Earth Observation (EO) technology has played an increasingly important role in determining various parameters characterising the land surface from space. This is because of its 43 44 advantages related to the speed at which data can be acquired (instantaneous updating of 45 information) by EO over large areas (synoptic views in a spatially contiguous fashion). Also, EO 46 overcomes many problems inherent to traditional data collection methods (e.g. access to otherwise 47 inaccessible areas). Additionally, remote sensing provides an efficient and cost-effective approach 48 for the systematic repeat-coverage of areas of interest without a disturbing influence on the area 49 (Kalivas et al., 2013). The advent of satellite-based EO, particularly over the last few decades, has 50 even reached a significant milestone in maturity that has allowed obtaining several land surface 51 parameters from spaceborne EO systems at an operational level (Srivastava et al., 2015). 52 Geostationary obit satellites are of particular interest to studying and monitoring Earth's physical 53 environment and the changes which occur by either anthropogenic activities or natural hazards. 54 The principal advantage of those satellites is that they are able to provide a width of spectral 55 information over large areas and at a time step compatible with the dynamics of several physical 56 processes of the Earth system.

57 The Spinning Enhanced Visible and Infrared Imager (SEVIRI) is a geostationary orbit imaging 58 radiometer which serves as the main payload on-board the Meteosat Second Generation (MSG) 59 satellite. This is a co-funded space mission between the European Space Agency (ESA) and 60 EUMETSAT. SEVIRI has 12 spectral channels, consisting of three Visible and Near-InfraRed (VNIR) channels (centred at 0.6, 0.8 and 1.6 µm), eight InfraRed (IR) channels (centred at 3.9, 6.2, 7.3, 8.7, 61 62 9.7, 10.8, 12.0 and 13.4 μ m) and one visible broadband channel (at 0.5–0.9 μ m) called the High Resolution Visible channel (HRV). The satellite provides image data at 3 km spatial resolution at the 63 64 sub-satellite point (nadir) for standard channels, and down to 1 km for the HRV channel, over 4 specific geographical regions (Europe, Africa - North_Africa and South_Africa- and South America), 65 66 with a baseline repeat cycle of 15 minutes. A series of operational products from SEVIRI are 67 provided by EUMETSAT and distributed by the Satellite Application Facility (SAF) on Land Surface Analysis (LSA) (http://landsaf.meteo.pt/). SEVIRI data are have been used in a range of 68 69 applications for example, solar modeling (Boojanowsi et al., 2013) agriculture studies (Eerens et al., 70 2014) and wildfires (Carvalheiro et al., 2010), meteorological studies (Ginoux et al., 2004). Yet, 71 despite the large geographical coverage of SEVIRI data acquisition globally, to our knowledge, at 72 present there is no software platform available to assist with the pre-processing of those 73 operational products, which would in turn allow their dissemination to a wider spectrum of 74 prospective users.

In purview of the above, herein we present an open source and stand-alone software tool, developed in Java, which allows performing basic, yet of key importance, pre-processing steps to the SEVIRI operationally distributed products. Our software platform, named "SEVIRI PrePro", makes also use of present day multi-core processors, being able to process fast very large datasets, making it also suitable for use in a High Performance Computing (HPC) environment. Furthermore, 80 we demonstrate the practical applicability of this tool using as an example an operationally

81 distributed product from SEVIRI, although equally any other operational product could be used.

82 2. THE SEVIRI PRE-PRO TOOLKIT

83 2.1 Introduction to the toolkit

84 The SEVIRI PrePro tool is a Java 8 (Gosling et al., 2014) based cross-platform tool that enables the 85 user to extract information (i.e. geophysical quantities of interest) from a SEVIRI product file. 86 SEVIRI product files come in HDF5 hierarchical format and each granule contains an image but 87 instead of typical RGB imaging which assigns a vector of R, G and B values per image site, a vector of 88 values corresponding to geophysical parameters is contained in this image. These values are 89 sampled per image site which is part of the image grid. There can be four grids, one per region. The 90 sites on the grid correspond to pairs of latitude and longitude and are indexed as in a typical image 91 by image coordinates constrained by the width and height of the image. The translation from the 92 grid (image) co-ordinates to region specific WGS84 coordinates is implemented through a list of 93 region specific files that one has to download from the LSA SAF site after registration. The user of 94 the tool can select various geographical sites from which can export, in batch mode, from near 95 image sites, the corresponding image vector irrespective of operational product. This is facilitated 96 by a convenient GUI. For HPC (High Performance Computing) reasons, a headless option has also 97 been developed and is also available which comes through a Command Line Interface (CLI). 98 Moreover the user can export via a Region of Interest (ROI) parts of the image. In SEVIRI PrePro the 99 exporting is done in the native format of BEAM/VISAT open source software platform (Brockman, 100 2003), namely BEAM DIMAP format, for compatibility reasons. The tool automates the batch 101 exporting through a ROI defibed ny a shape file (.shp). The user workflow is also easy to implement. 102 Thanks also to recent Java releases, SEVIRI PrePro is able to take advantage of all processors 103 installed in a given computer system. This way, the pre-processing is multithreaded and efficient in 104 performance.

105 2.2 Software Installation Requirements

106 To execute SEVIRI PrePro, first the static HDF5 (Folk et al., 2011) files for the region of interest 107 need to be downloaded, which are provided by LSA-SAF (Cihlar et al., 1999), subject to registration 108 to their site. Once this step is completed, the user will need to authorise their account before they 109 can request the necessary static files. Using this authorisation the user can download the necessary 110 files located in the "Auxiliary Data" tab. On the website is a list of .bz2 files in HDF5 format. The user 111 is advised to download all available files and store them in a folder since it can be used for further 112 reference. The structure of the folder is illustrated in Figure 1. After the HDF5 data have been 113 acquired, Java 8 needs to be installed to take advantage of speed and Graphical User Interface (GUI) 114 available through Java FX improvements. The installation has been tested with the corresponding 115 JDK (at time of writing JDK 8u60 was the most up to date version and used in implementation).

116

117 2.3 Installation of the SEVIRI PrePro Toolkit

The SEVIRI PrePro has been developed as open source software, released under the terms of the GNU General Public Licence, distributed by Aberystwyth University, United Kingdom (<u>www.aber.ac.uk/seviriPrePro</u>). The software tool is under GPLv3 and the user can either download the source code or build it using Eclipse (for Java developers) or download a binary

- 122 release from the same site. In order to build it from source, the user needs a BEAM/VISAT compiled
- 123 in Java 8 by using the corresponding build. The preferred way is to use a pre-compiled binary,
- 124 which is available as a 7z file download. The toolkit download contains three launchers, the main
- .jar file, a sample file in the Comma-Separated Values (CSV) (Shafranovich, 2005) format for pixel
 extraction, a folder with jar dependencies and a folder with shape files (Figure 2).
- 127

128 2.4 SEVIRI PrePro Implementation

129 2.4.1 The Graphical User Interface (GUI)

130 The user should first update (if necessary) the runGUI.bat file. Java location and assigned memory 131 can be modified. The defaults are a user wide installation of Java and 2048 MB of assigned memory. 132 If the environment is Linux, the user can copy and paste the instruction at the shell prompt and 133 execute it. A GUI appears as shown in Figure 3. One can immediately see that the tabbed interface 134 at the bottom offers two utilities. The first is the "Country Export" and the other one is "Pixel 135 Extraction". The generic part of the application allows one to re-project the whole products in the 136 Equirectangular, plate carrée projection (Snyder, 1993) which is a slow process. In the next 137 sections each of the three interfaces of the main toolkit menu shown in Figure 3 will be explained.

138 2.4.2 Inputs Requirements

139 In the generic part of the toolkit application the user needs to fill some input parameters (Figure 4). 140 The user must first specify the folder where the re-projected BEAM DIMAP files will be saved. The 141 user has also to provide the folder of the LSA SAF static files in order to achieve the grid translation. 142 Then the user must specify where the SEVIRI product files reside. The folder must have a flat 143 structure as no recursive searching has been implemented. Finally, the region the files belong must 144 be given. The assumption is that all the files in the folder have to do with the same region. One can 145 start the re-projection process which is very slow. We re-use the procedure in the BEAM VISAT API which is similarly slow. If the user needs a specific country re-projection, he should consult the next 146 147 sub-section. It does not matter if in the folder there is a mix of operational products. The BEAM 148 output files preserve this information in their filename.

149 2.4.3 Country Export Option

150 In order to export country specific information, the generic section must be already configured as 151 above. Country specific re-projection and export can be accomplished by loading the list of 152 countries from the CountriesSHP folder in the distribution. One has to select the shape file as shown 153 in Figure 5. The drop down list of countries is populated and the user can localize the re-projection 154 to the specific selected country. These countries through the grid translation, act as ROIs. A list of 155 BEAM DIMAP files will be the result containing only the part of the image that corresponds to the 156 country as opposed to the full region re-projection of the generic section. A typical run of the toolkit 157 is shown in Figure 5.

158 2.4.4 Pixel Extraction Option

159 In order to export country specific information, the generic section must be already configured as 160 above. Pixel extraction is another functionality provided by the SEVIRI tool. Each operational 161 product can be viewed as a vector sampled at grid sites. The aim is to find samples close to the 162 samples and extract the vectors as extracted site values. Figure 6 shows the main parametrisation. 163 One has to load a CSV file containing sites for which to extract values. The format of this file is given 164 in Table 1, where an example (included in the distribution) is displayed. These sites maybe far away 165 from sites. In order to determine the "farness" rule we resorted to a simple heuristic. The Vincenty 166 distance (Vincenty, 1975) is calculated between this site and all the samples. The closest sample is 167 selected. If the distance is less than 1 km then the site is included in the output with the values of 168 this closest sample. The input CSV format required to be followed is shown in the code listing of Figure 7. The output is stored in a series of CSV files, each for every type of operational product in 169 170 the SEVIRI files folder. This is necessary because of the uniformity of CSV file format. In this respect 171 an ET or LST (for example) CSV file is created. This tool is also offered as a CLI tool option. The CLI 172 tool serves for pixel extraction without using a GUI. For this reason, it can run in HPC environments 173 in parallel in order to accelerate the pixel extraction process. Pixel extraction workflows are offered 174 for both SEVIRI and ASCAT products. Two batch files are provided as customization guides to the 175 user. They share similar concepts. Table 2 shows the user provided customisations to the 176 command line SEVIRI pixel extraction.

177

178 3. SEVIRI Pre-Pro DEMONSTRATION

179 In this part, the use of SEVIRI PrePro is demonstrated in a real case study. The case study 180 demonstrates how the SEVIRI PrePro software tool can be used to perform basic pre-processing in 181 this particular operational product. It further demonstrates how a robust validation of the product 182 accuracy can be conducted using our tool (and HPC facilities if available), provided that reference 183 observations are available from ground measurements. As an example is used the SEVIRI 184 Evapotranspiration (ET) operationally distributed product (Ghilain et al., 2011), although equally 185 any other SEVIRI operational product distributed from LSASAF can be used. Concurrent ground 186 measurements of ET from a selected European site belonging to the CarboEurope ground 187 observational network (Baldocchi et al., 2003) are also used to demonstrate how comparison 188 against some reference data, if available, can easily be done.

189 **3.1 Datasets Description**

190 3.1.1 SEVIRI ET Product

191 For the purposes of the demonstration of SEVIRI PrePro capabilities the SEVIRI instantaneous ET 192 product (MET) was acquired for the Euro region of the Meteosat disk for the years 2010 and 2011. 193 This is one of the operational products from SEVIRI, which are all readily distributed at no cost, by 194 the Satellite Application Facility (SAF) on Land Surface Analysis (LSA) (http://landsaf.meteo.pt/). 195 In this product, ET is operationally estimated every 15 minutes from the SEVIRI radiometer, 196 whereas a daily ET flux operational product is also generated with a lag time of one day at a spatial 197 resolution of 1 km. These two products are provided for the full disk divided in four sub regions 198 through the LSA-SAF or via EUMETCast. The technical details concerning the technique 199 implemented for computing ET in this operational product can be found in Ghilain et al., (2011).

200 3.1.2 Study Site Characteristics & In-Situ

In-situ data for the complete years 2010 and 2011 were also acquired from the Spanish ES_Agu *open shrubland* CarboEurope site (36.9406N, -2.0329E). This site is located at an elevation of ~ 200 m asl and is situated in an area of arid steppe climate. Fr this particular site *in-situ* data was obtained from the CarboEurope website (<u>http://gaia.agraria.unitus.it/</u>). For the purpose of this

- 205 demonstration, those included primarily the *in-situ* measurements of ET and air temperature (Tair)
- as well as a number of other micrometerological parameters acquired for the same period (i.e. full
- 207 years 2010 and 2011 at 30' time step).

208 3.2 SEVIRI ET Dataset Pre-Processing

209 Using SEVIRI Pre-Pro tool, the ET product acquired for the Euro region of the Meteosat disk was 210 first reprojected from Normalized Geostationary Projection (NGP) to a regular latitude/longitude 211 grid and tailored from the full disk image to the study region (34°-45°N, 11°W-5°E). Subsequently, 212 using again SEVIRI PrePro each image granule was clipped into the European country on which our 213 experimental site was located. Following this, periods for which more than 10 % of each of the half-214 hour SEVIRI estimated ET (granules) were missing from a "site-day" were omitted from the 215 comparisons. The data was further refined by excluding granules with negative values from the 216 dataset. These values corresponded to flags or no-data values which were inappropriate for use in 217 assessing the agreement between both datasets. In addition, a scaling factor was applied to each 218 MET 30' product to derive the actual ET value from it (MSG-2 ET Product ATBD, 2008). 219 Subsequently, the *in-situ* ET values that corresponded to the date/time of the SEVIRI ET product 220 overpass were extracted (using an Excel MacroVBA), and assigned to point shapefiles of the test 221 sites, where there was one shapefile per country (tabular join in ArcMap 10.1). These shapefiles 222 were overlaid to the pre-processed SEVIRI images in the SEVIRI PrePro tool. Subsequently, the in-223 situ ET was matched against the SEVIRI ET of the pixel containing the site point. These pixels were 224 then extracted using SEVIRI PrePro to excel for further analysis and comparisons against the *in-situ* 225 data. An example of finally pre-processed products using SEVIRI PrePro are shown in Figure 7.

226 **3.1.3 SEVIRI ET vs in-situ Results**

227 Agreement between the SEVIRI ET operational product estimates and the corresponding in-situ 228 data was evaluated based on direct point by point comparisons. Several statistical performance 229 assessment metrics were used to evaluate the agreement between the compared datasets (Table 3) 230 These statistical metrics have been prominently used in analogous validation experiments of 231 relevant operational products validation studies (e.g. LSA-SAF Validation Report 232 Evapotranspiration Products, 2010). Table 4 shows the key statistics related to comparisons of 233 predicted and observed rates of ET over the ES_Agu experimental site for all days of comparison for 234 the years 2010 and 2011 individually, and also when the study days for both years were combined. 235 Figure 8 illustrates the agreement between the two datasets for years 2010 and 2011 separately, displaying the annual trends in the data. In general, the error metrics (Table 4) returned a low 236 237 RMSD and MAE of 0.035 mm h⁻¹ and 0.021 mm h⁻¹ respectively, suggesting the SEVIRI ET product 238 was able to estimate the *in-situ* measurements to a high degree of accuracy. Evidently, the low bias 239 (-0.01 mm h⁻¹) and scatter (0.035 mm h⁻¹) results indicate a stable estimation of the observed by 240 SEVIRI and suggest that the RMSD is derived predominantly from the scatter and not the bias. 241 Correlation coefficient results, although not as strong as the error metrics results, indicated a 242 strong correlation between the compared datasets (R – 0.655). In the 2010 comparisons (Table 4 243 and Figure 8), the bias is low for the ES_Agu site (0.03 mm h⁻¹) with almost no divergence from the 244 *in-situ*. In contrast, for the 2011 results (Table 4 and Figure 8) a much larger underestimation is 245 evident (-0.024 mm h⁻¹). However, results from both individual years indicate a stable and precise product estimation of the observed ET. RMSDs for both years are 0.036 mm h⁻¹ and 0.045 mm h⁻¹ 246 247 for 2010 and 2011 respectively, with the product again performing better during 2010. Adversely 248 to all other statistical metrics, the correlation coefficient was indeed greater for the 2011 results. 249 Previous examinations into the performance of the SEVIRI algorithm over a range of land cover

types in Europe have also returned comparable results to those presented herein. For example, Ghilain et al. (2011) evaluated the performance of the operational products algorithm over six European sites. Their study showed comparable results sites of short vegetation cover (RMSD ranging between 0.07 to 0.1 mm h⁻¹). More recently, Petropoulos et al., (2015b) evaluated the SEVIRI ET estimates against *in-situ* data for 9 sites form the CarboEurope network.

The results reported here illustrate the successful implementation of the SEVIRI PrePro software tool in providing a simple, fast and efficient way to undertake the usually complex pre-processing of SEVIRI ET operational data. The fact that comparable, or even improved results have been reported within the case study illustrate that there is no-loss of accuracy when the tool is used in place of the more general methodologies usually implemented to pre-process the SEVIRI data, with the added benefit of ease of use and the fact it is more time-efficient and computationally less expensive.

261

262 4. CONCLUDING REMARKS

In this short communication paper a new software tool for the pre-processing EO data of geostationary orbit acquired from the SEVIRI sensor, named SEVIRI PrePro, was presented. Following the presentation of the software functionalities, a demonstration of its use in practice was furnished using actual data from the SEVIRI ET product acquired for 2 years worth of data as well as corresponding *in-situ* observations acquired at an experimental site in Spain.

268 The product, developed in Java, is able to perform simple, yet of key importance, pre-processing 269 steps which make the use of SEVIRI products much easier to use than ever before in many practical 270 applications and research alike. The tool, which is also offered open access, makes use of present 271 day multicore processors, being able to process fast very large datasets even for personal 272 computers, making it also suitable for use in a High Performance Computing (HPC) environment. 273 From an algorithmic and software development perspective, a further advantage is the tools' ability 274 for inclusion of key functionalities such as shapefile incorporation for points or areas extraction, 275 which also results in highly robust and accurate results from the tool implementation. Its 276 application also allows for the analysis of a large amount of data from a single or multiple 277 operational products, developing a long time series analysis of those data yet requiring much less 278 effort and user expertise in comparison to more general methodologies (e.g. by a Matlab routine). 279 Finally, SEVIRI PrePro is robust and adaptable to be potentially integrated with other EO data, and, 280 as it is realised under GPL v3, in theory anybody can contribute changes or suggest features, which 281 consists a further advantage of the tool.

282

283 ACKNOWLEDGMENTS

This work has been funded by the FP7-People project "TRANSFORM-EO" as well as the High Performance Computing Facilities of Wales (HPCW) project "PREMIER-EO". Dr Petropoulos, as the PI of both projects, wishes to thank the funding bodies for supporting the implementation of this work. Authors are also grateful to the CarboEurope site managers and to the SEVIRI LSA-SAF team for the provision of the data supported the implementation of this study.

- 289
- 290 **REFERENCES**

291 Baldocchi, D. D. (2003): Assessing the eddy covariance technique for evaluating carbon dioxide exchange rates of ecosystems: past, present and future. Global Change Biology, 9(4), 479-292 293 492. 294 Bojanowski, Jędrzej S., Marcello Donatelli, Andrew K. Skidmore, Anton Vrieling (2013): An 295 auto-calibration procedure for empirical solar radiation models, Environmental Modelling 296 & Software, 49, pp 118-128. 297 Carvalheiro, L.C., S.O. Bernardo, M.D.M. Orgaz, Y. Yamazaki (2010): Forest Fires Mapping and 298 Monitoring of current and past forest fire activity from Meteosat Second Generation Data, 299 Environmental Modelling & Software, 25 (12), pp 1909-1914. 300 Cihlar, J., A. Belward, Y.M. Govaerts (1999): Meteosat second generation opportunities for land 301 surface research and applications, EUMETSAT Scientific Publications Drucherei Drach, 302 Germany (1999) EUM SP 01. 303 Destouni, G., Jaramillo, F., & Prieto, C. (2013): Hydroclimatic shifts driven by human water use for food and energy production. Nature Climate Change, 3, 213–217. 304 305 Eerens, H. D. Haesen, F. Rembold, F Urbano, C. Tote, L. Bydekerke (2014): Image time series 306 processing for agriculture monitoring. Environmental Modelling & software, 53, pp154-307 162. 308 Folk M, Heber G, Koziol Q, Pourmal E, Robinson D (2011): An overview of the HDF5 technology 309 suite and its applications. Proc. EDBTICDT 2011 Work Array Databases Pages 36–47 310 Ghilain, N., Arboleda, A., & Gellens-Meulenberghs, F. (2011): Evapotranspiration modelling at 311 large scale using near-real time MSG SEVIRI derived data. Hydrology and Earth System 312 Sciences, 15, 771-786. 313 Ginoux, P., J.M. Prospero, O. Torres, M. Chin (2004): Long-term simulation of global dust 314 distribution with the GOCART model: correlation with North Atlantic Oscillation, Environmental Modelling & Software, 19 (2), PP 113-128. 315 316 Kalivas, D., Petropoulos, G.P., Athanasiou, I. & V. Kollias (2013): An intercomparison of burnt 317 area estimates derived from key operational products: analysis of Greek wildland fires 318 2005-2007. Non-linear Processes in Geophysics, 20, 1-13, doi: 10.5194/npg-20-1-2013. 319 LSA-SAF Validation Evapotranspiration, report (2010): http://landsaf.meteo.pt/algorithms.jsp;jsessionid=AE4DA8FBC47A8ABA27F5891A9C1D 320 DB7D?seltab=7&starttab=7 [accessed on January, 14th, 2016]. 321 322 Mason, N., & Calow, R. (2012): Water security: from abstract concept to meaningful metrics. 323 Work. Pap. 357. 324 Petropoulos, G.P., G. Ireland, A. Cass & P.K. Srivastava (2015b): Performance Assessment of the 325 SEVIRI Evapotranspiration Operational Product: Results Over Diverse Mediterranean 326 Ecosystems IEEE Sensors, [in press], DOI 10.1109/JSEN.2015.2390031. 327 Shafranovich, Y., (2005): "Common Format and MIME Type for Comma-Separated Values (CSV) 328 Files", RFC 4180, DOI 10.17487/RFC4180, October 2005, <http://www.rfc-329 editor.org/info/rfc4180. 330 Snyder J.P., (1993): Flattening the Earth: Two Thousand Years of Map Projections, pp. 5-8, ISBN 331 0-226-76747.

- 332 Srivastava, P.K., Han, D., Islam, T., Petropoulos, G.P., Gupta, M. & Q. Dai (2015): Seasonal 333 evaluation of Evapotranspiration fluxes from MODIS Satellite and Mesoscale Model 334 Downscaled Global Reanalysis Datasets. Theoretical and Applied Climatology, pages 1-14, 335 DOI 10.1007/s00704-015-1430-1. 336 Vincenty, T. (April 1975a): "Direct and Inverse Solutions of Geodesics on the Ellipsoid with app 337 lication of nested equations" (PDF). Survey Review. XXIII (misprinted as XXII) (176): 88-338 93. Retrieved 2009-07-11. 339 Wood, E. F., Roundy, J. K., Troy, T. J., Van Beek, L. P. H., Bierkens, M. F., Blyth, E., ... & Whitehead, 340 P. (2011): Hyper-resolution global land surface modeling: Meeting a grand challenge for 341 monitoring Earth's terrestrial water. Water Resources Research, 47(5). 342
- 343

O The state	uter • Local Disk (C) • workspace • aberystwynn-projects • _Opensources	EVINE • SHARE_HEAS_room	-		•
rganize = Include	in library - Share with - Burn New folder				JII + CH 4
Favorites	Name	Date modified	Туре	Size	
E Desktop	HDF5_LSASAF_MSG_LAT_Euro_2bytesPrecision	4/24/2015 11:13 AM	File	2,172 KB	
Downloads	HDF5_LSASAF_MSG_LAT_Euro_4bytesPrecision	4/24/2015 11:15 AM	File	4,335 KB	
1 Recent Places	HDF5_LSASAF_MSG_LAT_MSG-Disk	4/24/2015 11:20 AM	File	26,920 KB	
Cropbox	HDF5_LSASAF_MSG_LAT_NAfr_2bytesPrecision	4/24/2015 11:16 AM	File	4,980 KB	
La Google Drive	HDF5_LSASAF_MSG_LAT_NAfr_4bytesPrecision	4/24/2015 11:17 AM	File	9,951 KB	
	HDF3_LSASAF_MSG_LAT_SAfr_2bytesPrecision	4/24/2015 13:17 AM	File	2,826 KB	
Libraries	HDF5_LSASAF_MSG_LAT_SAfr_4bytesPrecision	4/24/2015 11:17 AM	File	5,644 KB	
Documents	HDF5_LSASAF_MS6_LAT_SAme_2bytesPrecision	4/24/2015 11/21 AM	File	2,078 KB	
Music	HDFS_LSASAF_MSG_LAT_SAme_4bytesPrecision	4/24/2015 11:17 AM	Film	4,147 KB	
Pictures	HDF5_LSASAF_MSG_LON_Euro_2bytesPrecision	4/24/2015 11:15 AM	File	2,172 KB	
Subversion	HDF5_LSASAF_MSG_LON_Euro_4bytesPrecision	4/24/2015 11:15 AM	File	4,325 KB	
Videos	HDF5_LSASAF_MSG_LON_MSG-Disk	4/24/2015 11:21 AM	File	36,920 KB	
	HDF5_LSASAF_MSG_LON_NAfr_2bytesPrecision	4/24/2015 11:17 AM	File	4,980 KB	
Computer	HDF5_LSASAF_MSG_LON_NAfr_4bytesPrecision	4/24/2015 11:17 AM	File	9,951 KB	
Local Disk (C:)	HDF5_LSASAF_MSG_LON_SAfr_2bytesPrecision	4/24/2015 11:17 AM	File	2,826 KB	
	HDF5_LSASAF_MS0_LON_SAfr_4bytesPrecision	4/24/2015 11:17 AM	File	5,644 KB	
Network	HDF5_LSASAF_MSG_LON_SAme_2bytesPrecision	4/24/2015 11:17 AM	File	2,078 KB	
	HDF5_LSASAF_MSG_LON_SAme_AbytesPrecision	4/24/2015 11:17 AM	File	4.147 KB	
18 items					
Contraction of the second					

Figure 1: Folder structure of static HDF5 translation files in SEVIRI PrePro

	day a Local Rick (Cd. a Days & FITLES)	andrea distante to			
Compe	wer i Locaronsk (c.) i osers i rinnis i	sevinus_uistro •			
rganize • Include	in library Share with Burn	New folder			F • 0 •
Favorites	Name	Date modified	Туре	Size	
E Desktop	L CountriesSHP	10/1/2015 2:42 PM	File folder		
Downloads	🎍 sevirus_Eb	10/1/2015 2:03 PM	File folder		
E Recent Places	places	4/28/2015 5:54 PM	CSV File	1 KB	
Stopbox	🔜 runGUt	10/1/2015 2:06 PM	Windows Batch File	1 KB	
L Google Drive	In nunnerASCAT	5/6/2015 1:20 PM	Windows Batch File	1 KB	
	🔤 runnerSEVIRI	7/13/2015 12:19 PM	Windows Batch File	1 KB	
Libraries	sevinitool	10/1/2015 2:03 PM	Executable Jar File	55 KB	
Documents					
Music					
Pictures					
Subversion					
Videos					
133					
Computer					
Local Disk (Ci)					
7 items					

 Sevin Tool 			linia - Con
Sanisi Puldar -		Safeet Fuldare	
Output fulfier :		[Select Rate:]	
State: LATACH Nam		(Safae (Falder)	
Saturt Region	Euron	Connect Subles	
Country export Post Echarchist			
Shape Ne		[Selective]	
Select a country		[Baset]	

Figure 3: SEVIRI Pre-Pro toolkit initial screen menu



Figure 4: Parameters for reprojection under the SEVIRI PrePro toolkit



Figure 5: Country export using the SEVIRI PrePro toolkit



Figure 6: Pixel extraction with the GUI SEVIRI PrePro toolkit



Figure 7: Maps of the SEVIRI ET final pre-processed product using our SEVIRI Pre-Pro software here for August 6th, 2011 acquired at 2 different times of the day (7 am pm left and 11am right) for the ES_AGU site in Spain in the zoomed area.



Figure 8: A comparison between in-situ and predicted ET from SEVIRI for the different seasons for ES_AGU site years 2010 (top) and 2011 (bottom). Green represents the in-situ ET daily mean, Red is the SEVIRI-predicted ET, Blue is daily standard deviation of the in-situ ET.

site,lat,lon
ES_AGU,36.9406,-2.0329
ES_LJU,36.9283,-2.7505
IT_CAS,45.0700,8.7175
FR_MAU,43.3853,1.2922
IT_REN,46.5878,11.4347
UK_EBU,55.8660,-3.2058
IT_MBO,46.0296,11.0029
US_ELM,25.5519,-80.782
US_ME2,44.4523,-121.5574
US_NE3,41.1797,-96.4396
US_WHS,31.7438,-110.0522
US_TON,38.4316,-120.9660
US_VAR,38.4067,-120.9507
Howard_Springs,-12.495,131.15
Daly_Pasture,-14.06333,131.318056
Sturt_Plains,-17.15076,133.350317
Wallaby,-37.426222,145.18725
Tumbarumba,-35.489144,148.151667

Table 1: Sample pixel extraction specification in CSV format

Table 2: Example specification of sites for pixel extraction

The SEVIRI pixel extraction follows the same concepts like the GUI pixel extraction. The next listing **Error! Reference source not found.** of the batch file shows the similarity./* args[0] the data folder args[1] the csv of places args[2] the output folder args[3] static files */
set args_0=c:/downloads/SEVIRI

set args_1=C:/downloads/places.csv set args_2=C:/downloads/output set args_3=C:/downloads/Static_HDF5_Files

java -Xmx2048m -jar SEVIRItool.jar %args_0% %args_1% %args_2% %args_3%

Table 3: An overview of the statistical measures implemented in this study to evaluate SEVIRIET operational product predictions against the corresponding in-situ data for the ES_AGUexperimental site used in this study

Name	Description	Mathematical Definition		
Bias/MBE	Bias (accuracy) or Mean Bias Error	$bias = \frac{1}{N} \sum_{i=1}^{N} (P_i - O_i)$		
R	Linear Correlation Coefficient of Determination of P _i to O _i	$R = \begin{bmatrix} \sum_{i=1}^{N} (P_i - \overline{P})(O_i - \overline{O}) \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$		
Scatter/MSD	Scatter (precision) or Mean Standard Deviation	scatter = $\frac{1}{(N-1)}\sum_{i=1}^{N} (P_i - O_i - \overline{(P_i - O_i)})^2$		
RMSD	Root Mean Square Difference	$RMSD = \sqrt{bias^2 + scatter^2}$		
MAE	Mean Absolute Error	$MAD = N^{-1} \sum_{i=1}^{N} \left P_i - O_i \right $		

Table 4: Results from comparison between SEVIRI-predicted and in-situ ET estimates forES_Agu site in 2010, 2011.

Year	Bias	Scatter	RMSD	MAE	R
2010	0.003	0.035	0.036	0.022	0.684
2011	-0.024	0.038	0.045	0.030	0.546