

## Aberystwyth University

### *WRF-PDM*

Srivastava, P. K.; Islam, T.; Petropoulos, George; Gupta, M.

*Published in:*  
European Water

*Publication date:*  
2017

*Citation for published version (APA):*

Srivastava, P. K., Islam, T., Petropoulos, G., & Gupta, M. (2017). WRF-PDM: Prognostic approach for discharge prediction in ungauged catchment. *European Water*, 57, 129-132.

#### **General rights**

Copyright and moral rights for the publications made accessible in the Aberystwyth Research Portal (the Institutional Repository) are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the Aberystwyth Research Portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the Aberystwyth Research Portal

#### **Take down policy**

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

tel: +44 1970 62 2400  
email: [is@aber.ac.uk](mailto:is@aber.ac.uk)

# WRF-PDM: Prognostic approach for discharge prediction in ungauged catchment

P.K. Srivastava<sup>1\*</sup>, T. Islam<sup>2</sup>, G. Petropoulos<sup>3</sup> and M. Gupta<sup>4</sup>

<sup>1</sup> Institute of Environment and Sustainable Development, Banaras Hindu University, Varanasi, India

<sup>2</sup> NASA Jet Propulsion Laboratory, Pasadena, CA, USA

<sup>3</sup> Department of Geography and Earth Sciences, University of Aberystwyth, UK

<sup>4</sup> Department of Geology, University of Delhi, India

\* e-mail: prashant.just@gmail.com

**Abstract:** In this study, the mesoscale model WRF (Weather Research & Forecasting model) is used for dynamical downscaling of European Centre for Medium Range Weather Forecasts (ECMWF) ERA interim reanalysis global datasets for obtaining hydro-meteorological variables. The WRF estimated precipitation and Evapo-transpiration are then used as input data for the Probability Distributed Model (PDM) for discharge prediction. For performance evaluation of the integrated framework, objective function like Nash Sutcliffe Efficiency (NSE) is used. Analysis of NSE indicates values of 0.85 and 0.82 during the calibration and validation respectively for the combination observed rainfall and station based reference Evapotranspiration (ET<sub>o</sub>). On the other hand, a marginally lower performance is reported by the combination Observed Rainfall and WRF based ET<sub>o</sub> ( $NSE_{cal}=0.82$ ;  $NSE_{val}=0.80$ ), while a very poor performance is reported by the combination Rainfall and ET<sub>o</sub> when both derived from WRF ( $NSE_{cal}=0.58$ ;  $NSE_{val}=0.06$ ). The overall analysis suggests that the WRF-PDM can be used for discharge prediction in the absence of ground based measurements. This study provides valuable information to the hydro-meteorologist on downscaled weather variables from global datasets and its applicability to rainfall-runoff modeling for river discharge prediction.

**Key words:** WRF-PDM, GLUE, Rainfall-runoff, Discharge, Sensitivity Analysis and Uncertainty Estimation

## 1. INTRODUCTION

Precipitation and Reference Evapotranspiration (ET<sub>o</sub>) are considered as two important key variables for rainfall runoff modelling (Shukla and Mintz, 1982). The WRF model is used by many researchers in last decade and found to be promising for regional applications and development of operational numerical weather prediction (Lo *et al.*, 2008; Givati *et al.*, 2011). Recently, efforts have been made to estimate ET and precipitation using Weather Research and Forecasting model (WRF) (Bukovsky and Karoly, 2009; Skok *et al.*, 2010).

Among hydrological models, the lumped rainfall runoff model PDM (Probability Distributed Model) has been widely used in many parts of the world with satisfactory performances (Srivastava *et al.*, 2013). PDM model is developed by the UK Centre for Ecology and Hydrology by Moore in (Moore, 2007). The PDM model uses long records of flow and rainfall and provides a highly effective representation of the runoff generation process (Srivastava *et al.*, 2014). Because of its high performance it is also used in this study for discharge estimation.

In purview of the above, the main aim of this study is to examine the performance of WRF-PDM framework for discharge prediction with different input data conditions derived from global reanalysis datasets using WRF and station based measurements. This type of study is important to understand the model performances and their suitability for discharge prediction especially for ungauged catchments.

## 2. MATERIALS AND METHODOLOGY

The Brue catchment is located in the south-west of England and used as a case study in this work. The flow and rainfall datasets are provided by Environment agency, UK, while meteorological datasets are provided by the British Atmospheric Data Centre (BADC), UK. The hourly datasets from August 2010 to January 2012 are used for calibration and validation of the model. The global European Centre for Medium Range Weather Forecasts (ECMWF) ERA interim reanalysis data is used as forcing for Weather Research and Forecasting (WRF) model (<http://www.ecmwf.int/>). The latest WRF model is used in this study with the Advanced Research WRF (ARW) dynamic core (Powers, 2007; Schwartz *et al.*, 2009). The WRF model is centered over the Brue catchment with three nested domains (D1, D2 and D3). The innermost high resolution domain (D3) is used in this study. The outputs of WRF i.e. precipitation and ET are used as inputs in the lumped rainfall runoff model PDM (Probability Distributed Model) for discharge prediction. Total five PDM parameters -  $C_{\max}$  (maximum store capacity),  $b$  (exponent of pareto distribution),  $g$  (groundwater recharge time constant),  $K_f$  (fast flow component) and  $K_s$  (slow flow component) are used for model calibration.

## 3. RESULTS AND DISCUSSION

The WRF estimated precipitation and ETo are used as input for the Probability Distributed Model (PDM) for discharge prediction. Total three input data conditions are designed for assessing the WRF-PDM performance for discharge prediction as shown in Table 1.

Table 1. Different combinations used in this study

S.No.	Input conditions	Combinations
1	Set1	Observed Rainfall and Station based ETo
2	Set2	Observed Rainfall and WRF based ETo
3	Set3	Rainfall and ETo both from WRF

Sensitivity analysis is performed on the locally conditioned PDM model parameters  $C_{\max}$ ,  $b$ ,  $g$ ,  $K_f$  and  $K_s$ . After optimizing the PDM model parameters, the discharge by using the different combinations are estimated and the hydrographs are presented in Fig. 1.

The performance is depicted in terms of Taylor diagram as shown in Fig. 2. It provides a simpler way of presenting the model performances using the graphical interface by summarizing how closely the model simulated results match with the observations. The performances between the two datasets are quantified in terms of their correlation, their centered root-mean-square difference and the standard deviations. In calibration, poorest performance can be seen in case of set3, while set1 and set2 are mostly similar in prediction discharge. During the validation, the worst performance is reported by set3 and better in case of set1 and set2.

The analysis of objective function Nash Sutcliffe Efficiency (NSE) indicates values of 0.85 and 0.82 during the calibration and validation respectively (set-1). On the other hand, a marginally lower performance are reported by set-2 ( $NSE_{\text{cal}}= 0.82$ ;  $NSE_{\text{val}}= 0.80$ ), while a very poor performance is reported by set-3 ( $NSE_{\text{cal}}= 0.58$ ;  $NSE_{\text{val}}= 0.06$ ). The lower performance of set3 can be attributed to the poor simulation of WRF precipitation, which indicates that more work is needed

on improvement of parameterization schemes for discharge prediction.




Figure 1. Hydrographs obtained by using different combinations: (a) Calibration; (b) Validation




Figure 2. Taylor diagram showing the performance of different combinations: (a) Calibration; (b) Validation

The overall analysis suggests that the estimates in the predicted discharge using the WRF derived ET have comparable performance with the ground based observed datasets and hence promising for the discharge prediction in the absence of ground based measurements of ET.

## 4. CONCLUSIONS

The over application of WRF indicates that it is able to downscale the global data into much finer resolutions in space and time for hydro-meteorological applications. Further, it can be used in integration with PDM model for prediction of discharge. The different datasets used in this study indicates that the WRF downscaled meteorological variables can be used for ET. Further the quality of ET derived is better than the WRF simulated precipitation, which is also reflected by the simulated discharge. The overall analysis indicates that the WRF precipitation is least useful for discharge prediction and therefore better schemes or forcing are needed for precipitation. On the other hand, ET is giving satisfactory performance, when used with observed rainfall. This study can provide hydrologists with valuable information on downscaled weather variables from global datasets and its applicability for rainfall-runoff modeling.

## ACKNOWLEDGMENT

The authors would like to thank the Commonwealth Scholarship Commission, British Council, United Kingdom and Ministry of Human Resource Development, Government of India for providing the necessary support and funding for this research. The authors would like to acknowledge the British Atmospheric Data Centre, United Kingdom for providing the ground datasets.

## REFERENCES

- Bukovsky, M.S., Karoly, D.J., 2009. Precipitation simulations using WRF as a nested regional climate model. *Journal of applied Meteorology and Climatology* 48, 2152-2159.
- Givati, A., Lynn, B., Liu, Y., Rimmer, A., 2011. Using the WRF model in an operational streamflow forecast system for the Jordan River. *Journal of Applied Meteorology and Climatology* 51, 285-299.
- Lo, J.C.F., Yang, Z.L., Pielke, R.A., 2008. Assessment of three dynamical climate downscaling methods using the Weather Research and Forecasting (WRF) model. *Journal of Geophysical Research: Atmospheres* 113.
- Moore, R., 2007. The PDM rainfall-runoff model. *Hydrology and Earth System Sciences Discussions* 11, 483-499.
- Powers, J.G., 2007. Numerical prediction of an Antarctic severe wind event with the Weather Research and Forecasting (WRF) model. *Monthly Weather Review* 135, 3134-3157.
- Schwartz, C.S., Kain, J.S., Weiss, S.J., Xue, M., Bright, D.R., Kong, F., Thomas, K.W., Levit, J.J., Coniglio, M.C., 2009. Next-day convection-allowing WRF model guidance: A second look at 2-km versus 4-km grid spacing. *Monthly Weather Review* 137, 3351-3372.
- Shukla, J., Mintz, Y., 1982. Influence of land-surface evapotranspiration on the earth's climate. *Science* 215, 1498-1501.
- Skok, G., Tribbia, J., Rakovec, J., 2010. Object-based analysis and verification of WRF model precipitation in the low-and midlatitude Pacific Ocean. *Monthly Weather Review* 138, 4561-4575.
- Srivastava, P.K., Han, D., Ramirez, M.R., Islam, T., 2013. Appraisal of SMOS soil moisture at a catchment scale in a temperate maritime climate. *Journal of Hydrology* 498, 292-304.
- Srivastava, P.K., Han, D., Rico-Ramirez, M.A., Islam, T., 2013. Machine learning techniques for downscaling SMOS satellite soil moisture using MODIS land surface temperature for hydrological application. *Water Resour Manage.* 27(8), 3127-3144
- Srivastava, P.K., Han, D., Rico-Ramirez, M.A., Islam, T., 2014. Sensitivity and uncertainty analysis of mesoscale model downscaled hydro meteorological variables for discharge prediction. *Hydrological Processes* 28, 4419-4432.